

101 ExitCheck® Wall Mount Delayed Egress - NFPA 101 Locking Arrangements Distributor Discount Code **GKK**

Proprietary Verbal Exit Instructions with Alarm Tone and 3/4" Digital Countdown Display



STANDARD FEATURES INCLUDE: 12/24VDC voltage sensing input, delay electronics packaged on a 3-gang wall plate for recessed wall mounting or surface wall mounting with optional junction box. Features include: std. 15 or 30 second switchable exit delay (NA), 1 or 2 second nuisance delay. Keypad for violation reset, momentary bypass and on-off; Voice Annunciation and digital countdown display with door open indicator. Status and remote control inputs are standard.

12VDC / 24VDC @ 200 mA Max.

- Doors **WITH** latch assemblies are sensor activated and do not require power transfer or trigger switch in exit device. Where preferred a trigger switch may be added to the exit device for manual activation in lieu of door movement activation.
- Doors **WITHOUT** latches require a non-latching Request-to-Exit Bar PSB560 Sure Exit® or MSB550 Switch Bar (see page 77). Also compatible with standard EMLocks (see page 7.)



"Security Industry Finest"
ISC Expo

DELAYED EGRESS CONTROLLER (1 PER OPENING, SINGLE OR PAIRS)

LIST



101-DE

101-DE Wall mount controller with keypad control and reset, 200 mA @ 12/24 VDC - NA standard **848.00**

101-KDE Wall mount controller with both key switch and keypad control and reset, 200 mA @ 12/24 VDC **960.00**
order with optional Mortise Cylinder



CYL-6KDK 6 pin, 1.125" Mortise Cylinder, Keyed Different **add 33.00**

CYL-6KAQ 6 pin, 1.125" Mortise Cylinder, Keyed Alike **add 33.00**

Specify NA, NC, ND, BC, BD - see codes and description on page 18

Optional Add-On: If no Code is specified - NA is the SDC STANDARD OPERATIONS MODE for this product

RRX Reset on REX - No Charge when ordered WITH a 101-DE/KDE.

Allows the REX input to reset after an unauthorized egress alarm. Not available for NC operation. Replacement Chip (if ordered separately from 101-DE/KDE unit)

54.00



101-KDE

MAGNETIC LOCK WITH INTEGRATED ACTIVATION SENSOR

LIST

Specify 2 for pair of doors

1511DEV Single, 1650 lbs holding force, 670/350 mA @12/24 VDC **539.00**

1571DEV Single, 1200 lbs holding force Energy Saver, 250/125 mA @12/24 VDC **512.00**

1581DEV Single, 650 lbs holding force, 440/220 mA @12/24 VDC **427.00**

Outdoor Locks

1575DEU Single outdoor magnetic lock with magnetic bond sensor **512.00**

1576DEU Single face drilled outdoor magnetic lock with magnetic bond sensor **512.00**

1576DE-ZB Inswing mounting bracket for 1576DEU **161.00**



101-DE with DEC-J

MAGNETIC LOCK FINISH

Add to List

V 628 Clear Anodized Aluminum (Standard) **N/C**

Y Black Anodized Single **86.00**

Powder Coat Finishes

(a coating electrostatically applied to form a hard finish, that is tougher than conventional paint)

X Dark Bronze Powder Coat Painted (313/613 Equal) Single **86.00**



101-1AK


OPTIONAL MONITORING

Add to List

B Magnetic bond sensor, indicates locked with full holding force, low holding force, unlocked, tampering and obstructions. **(1581DE SPST only)** **65.00**

D Door position sensor, indicates door open and door closed. Commonly used to verify egress after alarm and exit delay activation. **44.00**

(D) Door position sensor not available with 1581, 1575 and 1576



DEC-J

OPTIONAL HARDWARE

Add to List

101-1AK Outdoor reset with LED and Audible annunciator. 2-gang outdoor box required **342.00**
(Interior 101-DE and 1575 or 1576 outdoor magnetic lock required)

DEC-J 3 Gang Interior surface mount box for 101-DE **97.00**

SHD-J Shroud for surface mount box DEC-J outdoor use **65.00**

SHD-J
End View



SHD-J with 101-DE

Mounting Kits & Angle Brackets - See page 11

SECURITY DOOR CONTROLS
801 Avenida Acaso • Camarillo, CA 93012
Email: Service@sdsecurity.com • www.sdsecurity.com



Delayed Egress Locks
& Controllers



918 Keyless Reset and Bypass or Momentary Authorized Access 500 User Codes **171.00**
Keypad tamper lockout; Indoor blue backlit, moisture resistant keypad



920 Keyless Reset and Bypass or Momentary Authorized Access 500 User Codes **188.00**
Heavy Cast Vandal Resistant Housing

920



702R Separate wall mount reset key switch assembly **118.00**
MO SPDT dry contact, 6 Amp @ 30VDC max.
Accepts standard 1-1/8" to 1-1/4" (*Mortise key cylinder not included*)



707R Remote reset key switch with dual function for Bypass (authorized egress) and reset **161.00**
(2) MO SPDT dry contact, 6Amp @ 30VDC max
Accepts standard 1-1/8" to 1-1/4" mortise key cylinder. (*Mortise key cylinder not included*)

707R



708R Remote reset key switch for bypass (on/off) and reset **161.00**
(1) Maintain (1) MO, SPDT dry contact, 6Amp @ 30VDC max
Accepts standard 1-1/8" to 1-1/4" mortise key cylinder. (*Mortise key cylinder not included*)

708R

order with optional Mortise Cylinder



CYL-6KDQ 6 pin, 1.125" Mortise Cylinder, Keyed Different **add 33.00**
CYL-6KAQ 6 pin, 1.125" Mortise Cylinder, Keyed Alike **add 33.00**



101-1A Remote or local single door annunciator with audible alarm and tricolor LED, 1 Gang **113.00**
Green - Secure Amber - Egress initiated Red - Door unlocked

101-1A



101-4AM Remote four door annunciator with audible alarm mute button. Four tricolor LEDs, 2 Gang **342.00**
Green - Secure Amber - Egress initiated Red - Door unlocked

101-4AM



101-1AK Remote or local single door annunciator with 2 function key switch for on/off, reset, **342.00**
audible alarm and tricolor LED, 2 Gang
Green - Secure Amber - Egress initiated Red - Door unlocked
Accepts standard 1-1/8" to 1-1/4" mortise key cylinder.
(*Mortise key cylinder not included*)

101-1AK

order with optional Mortise Cylinder



CYL-6KDQ 6 pin, 1.125" Mortise Cylinder, Keyed Different **add 33.00**
CYL-6KAQ 6 pin, 1.125" Mortise Cylinder, Keyed Alike **add 33.00**



101-PAM Remote single door annunciator with 3 push button switches for momentary **342.00**
access. On/off and audible alarm mute button with tricolor LED, 2 Gang
Green - Secure Amber - Egress initiated Red - Door unlocked
Recommended for remote installation only

101-PAM



101-SP External 15 watt speaker connects directly to 1511S or 1511T for enhanced decibels **40.00**
onsite or remote voice message annunciation. Speaker driver may be provided by others
for extreme decibel requirements.

101-SP



101-SPSN Remote Single Gang Annunciator with speaker and 80db tone. Duplicates ExitCheck alternat- **103.00**
ing voice message and tone.

101-SPSN