

602RF(A)(L) and 631RF(A)(L) tested according to UL Standard 1481, listing includes:

Access Control Systems Unit ALVY Burglar Alarm Systems Power Supply APHV
 Releasing Device Accessory SYSW Fire and Burglar Alarm Power Supply URTZ

632RF(A)(L) Access Control Systems Unit ALVY

632RF(A)(L), 634RF and 636RF UL listed as:
 General Purpose QQFU/QQFU7 Power Supply



SECURITY DOOR CONTROLS
 801 Avenida Acaso • Camarillo, CA 93012
 Email: Service@sdcsecurity.com • www.sdcsecurity.com

Price List Effective February 1, 2017

Power Supply & Door Controllers



602RFL



631RFL




632RFL



602RF / 631RF



632RF
 with optional power cord
 and 2 - CR4 modules



631RFA
 632RFA



634RF
 636RF



12VR

STANDARD FEATURES:

- Modular design
- Filtered and regulated output
- Field selectable 12/24VDC
- Fire/Emergency release input
- Field selectable manual reset input (n/a with 631RF(A))
- Input, output and battery LED status indicators
- Thermal and short circuit protection with auto reset
- Battery charger
- Low battery disconnect



FIELD SELECTABLE 12VDC OR 24VDC OUTPUTS

LIST

| | | |
|---------------|--|---------------|
| 602RFL | 1 Amp, class 2 output, less box | 218.00 |
| 602RF | 1 Amp, class 2 output, 12" W x 12" H x 3.75" D box | 270.00 |
| 602RFA | 1 Amp, class 2 output, 16" W x 14" H x 6.5" D box | 383.00 |
| 631RFL | 1.5 Amp, class 2 output, less box | 270.00 |
| 631RF | 1.5 Amp, class 2 output, 12" W x 12" H x 3.75" D box | 363.00 |
| 631RFA | 1.5 Amp, class 2 output, 16" W x 14" H x 6.5" D box | 435.00 |
| 632RFL | 2 Amp, class 2 output, less box | 321.00 |
| 632RF | 2 Amp, class 2 output, 12" W x 12" H x 3.75" D box | 414.00 |
| 632RFA | 2 Amp, class 2 output, 16" W x 14" H x 6.5" D box | 477.00 |
| 634RF | 4 Amp, field select one 4 Amp output, or two 2 Amp class 2 outputs | 621.00 |
| 636RF | 6 Amp, field select one 6 Amp output, or three 2 Amp class 2 outputs | 725.00 |

DUAL 12VDC AND 24VDC OUTPUT CAPABILITY

Add to List

| | | |
|-------------|--|--------------|
| 12VR | 500mA, 12VDC regulated and filtered output module With the power supply output set at 24VDC for locking devices and components, the addition of the 12VR provides a separate 12VDC 500 mA output for access controls or other 12VDC devices | 52.00 |
|-------------|--|--------------|

OPTIONS

Add to List

| | | |
|------------------|---|---------------|
| MR | Cover mounted manual reset switch for Fire/Emergency release <i>(not available on 631RF)</i> | 38.00 |
| PS-1 | System On-Off push switch inside power supply enclosure | 38.00 |
| PS-1A | System On-Off push switch on enclosure cover | 38.00 |
| 14-2 | 7 day - skip a day programmable timer. Automatically unlocks and locks all doors or specific doors on programmed days only. | 249.00 |
| PC | 6 ft. power cord. Recommended for 1 Amp and 1.5 Amp, eliminating the need for AC conduit | 38.00 |
| KL | Key lock cover | 38.00 |
| 220V/230V | 230VAC, 50/60Hz | N/C |