


GWXT Auxiliary Locks CVXJ Burglary Resistant Electrically Operated Door Lock



UL10C Positive Pressure Compliant
UBC Classified in accordance with Uniform Building Code standard 7-2 "Fire Test for Door Assemblies"



1561



1562



1565



1566

FEATURES

- Door static and relock sensor, detects door is closed, at rest and aligned before relocking
- Automatic voltage sensing input
- Lateral and vertical alignment adjustment
- Floating armature with alloy steel shear tabs
- 1561 and 1562: 650/350 mA @ 12/24VDC Auto-Sensing
- 1565 and 1566: 800/400 mA @ 12/24VDC Auto-Sensing

ELECTRICAL SPECIFICATIONS

CONCEALED HI/SHEAR EMLOCK LIST

2,000 Lbs. Holding Force, 8" x 1-1/2" Lock

| | | |
|-------------|--|---------------|
| 1561 | 1-5/8" depth, integrated electronics for 1-3/4" to 2" frames | 792.00 |
| 1562 | 1-1/4" depth, with external electronics, for 1-1/4" to 1-3/4" frames | 792.00 |

2,700 Lbs. Holding Force, 10-7/16" x 1-1/2" Lock


| | | |
|-------------|---|---------------|
| 1565 | 1-5/8" depth, integrated electronics, for 1-3/4" to 2" frames | 860.00 |
| 1566 | 1-1/4" depth, external electronics, for 1-1/4" to 1-1/2" frames | 860.00 |

SPECIFY ARMATURE

Armature supplied with lock. Specify type required:

- 1565/1566** ITC, FTC or HTC
- 1561/1562** ITCM, FTCM or HTC

| | | |
|-------------|--|---------------|
| ITC | Standard mounting armature kit for aluminum and hollow metal doors with 7/8" to 1-1/8" deep top channels, wood doors and factory prepared hollow metal flush edge doors. | N/C |
| ITCM | | |
| FTC | Mounting kit for field prepared horizontal mounting in hollow metal doors with flush edge. | N/C |
| FTCM | | |
| HTC | Mounting kit for 1-15/16" deep herculite channels | N/C |
| HTCM | | |
| HTR | Herculite top rail armature adjustment bracket for leading edge adjustments. | 352.00 |
| HTRM | | |



HTR

ADD ONS Add to List

| | | |
|--------------|---|---------------|
| BA | Bond sensor indicates proper armature contact and reduced holding power due to improper armature contact or tampering. SPDT 0.25 Amp maximum (<i>not available on 1562 and 1566</i>) | 114.00 |
| DPS | Door position switch indicates door open or closed. SPDT 0.25 Amp maximum. | 52.00 |
| L3 | External LED status indicator, mounts separately through the frame and may be used to indicate lock is energized or wired to BAS bond sensor for door status. | 17.00 |
| WDRB | Wood door reinforcement box for 1565 and 1566 | 42.00 |
| WDRBM | Wood door reinforcement box for 1561 and 1562 | 42.00 |



WDRB

EMLock®
Lifetime Warranty



ANSI/BHMA A156.23
Grade 1



3774-0324:100

MEA
City of New York

768-80-SA

Price List Effective February 1, 2017



1562SC



1562SCHDB



1561S



1561TJ

SEMI-CONCEALED HI/SHEAR EMLOCKS LIST

2,000 Lbs. Holding Force, 8" x 1-1/2" x 1-1/4" Lock

| | | |
|---------------------|---|-----------------|
| 1562SC | 1-1/4" depth, with external electronics, for 1-1/4" to 1-3/4" For Hollow metal frames | 932.00 |
| 1562SCHDB1/2 | 1-1/4" depth, with external electronics, for 1-1/4" to 1-3/4" frames For 1/2" Herculite full glass doors | 1,155.00 |
| 1562SCHDB3/4 | 1-1/4" depth, with external electronics, for 1-1/4" to 1-3/4" frames For 3/4" Herculite full glass doors. | 1,115.00 |

SURFACE MOUNT HI/SHEAR EMLOCKS LIST

2,000 Lbs. Holding Force, 8" x 1-3/4" x 1-3/4" Lock For Hollow metal frames and wood or hollow metal doors

| | | |
|---------------|--|----------------|
| 1561S | Surface mount for the push side of the door with integrated electronics | 1098.00 |
| 1561TJ | Surface top jamb mount for the pull side of the door with integrated electronics | 1098.00 |

STANDARD FINISH Add to List

| | |
|--------------------------------|--------------|
| V 628 Anodized Aluminum | N/C |
| Y Black Anodized | 63.00 |

Powder Coat Finishes (a coating electrostatically applied to form a hard finish, that is tougher than conventional paint)

| | |
|--|--------------|
| X Dark Bronze Powder Coat Painted | 83.00 |
| C Brass Powder Coat Painted | 63.00 |

Plated Finishes - Special order, no cancellation, no returns

| | | |
|----------------------------|--------------------------|---------------|
| P 625 Bright Chrome | Q 626 Dull Chrome | 197.00 |
|----------------------------|--------------------------|---------------|

OPTIONS Add to List

| | | |
|------------|---|---------------|
| BA | Bond sensor indicates proper armature contact and reduced holding power due to improper armature contact or tampering. SPDT 0.25 Amp maximum) | 114.00 |
| DPS | Door position switch indicates door open or closed. SPDT 0.25 Amp maximum. | 52.00 |
| L3 | External LED status indicator, mounts separately through the frame and may be used to indicate lock is energized or wired to BAS bond sensor for door status. | 17.00 |

Magnetic Locks

