



FWAX Special Locking Arrangements  
GWXT Auxiliary Locks

ANSI/BHMA A156.24  
Grade 1



3774-0324:103



1581S

**SDC** PUSH UNTIL ALARM SOUNDS. DOOR CAN BE OPENED IN 15 SECONDS.

**1581S** Single Mini Delayed Egress Lock 650 lbs. holding force. Current: 320/500 mA @ 24VDC/12VDC **932.00**

Specify 2 for pairs of doors  
Remote reset control required. See below.  
Lock size 10" L x 2" H x 2.375" D

SPECIFY OPERATION

Specify **ND, NC, NH, BC, BD, BH** - see codes and description on page 18  
If no Code is specified - **ND** is the **SDC STANDARD OPERATIONS MODE** for this product

SPECIFY FINISH      Add to List

**Anodized Finishes**

<b>V</b>	628 Clear Anodized Aluminum (standard)	<b>N/C</b>
<b>Y</b>	335 Black Anodized	<b>83.00</b>

**Powder Coat Finishes**

(a coating electrostatically applied to form a hard finish, that is tougher than conventional paint)

<b>X</b>	Dark Bronze Powder Coat Painted (313/613 Equal)	<b>83.00</b>	<b>C</b>	605 Bright Brass Powder Coat Painted	<b>83.00</b>
<b>D</b>	606 Dull Brass Powder Coat Painted	<b>83.00</b>			

**Plated Finishes. Special order, no cancellations or returns**

<b>P</b>	625 Bright Chrome	<b>197.00</b>	<b>Q</b>	626 Dull Chrome	<b>197.00</b>
----------	-------------------	---------------	----------	-----------------	---------------

SPECIFY OPTIONS      Add to List

<b>D</b>	Door position status	<b>63.00</b>
<b>B</b>	Magnetic bond sensor (Not an output. Low Holding Force. Put unit into alarm.)	<b>104.00</b>

TANDEM CABLE FOR PAIR OF DOORS      LIST

**Required when using two locks on a pair of doors, cables enable slave operation.**

<b>1581S-TC-3</b>	Cable kit for connecting two locks through the frame header	<b>32.00</b>
<b>1581S-TC-10</b>	Cable kit for connecting wiring for two locks in a remote junction box	<b>42.00</b>

SPECIFY RESET AND CONTROL DEVICE      LIST

Select Reset Station for NC and ND functions

<b>918</b>	EntryCheck™ digital keypad, 500 user codes Keyless Reset / manual power up / bypass	<b>166.00</b>
<b>728</b>	Key switch, 2 keys, 1 gang Reset / manual power up / sustained bypass	<b>63.00</b>
<b>728L3</b>	Key switch, 2 keys, 1 gang, LED status indicator Reset / manual power up / sustained bypass	<b>87.00</b>
<b>702R</b>	Separate wall mount reset key switch assembly MO SPDT dry contact, 6 Amp @ 30VDC max. Accepts standard 1-1/8" to 1-1/4" (Mortise key cylinder not included)	<b>114.00</b>
<b>101-1AK</b>	Key switch assembly, 2 gang, LED status indicator, less cylinder Reset / manual power up / sustained bypass	<b>332.00</b>
<b>101-4AM</b>	Four station remote annunciator	<b>332.00</b>



**SECURITY DOOR CONTROLS**  
801 Avenida Acaso • Camarillo, CA 93012  
Email: Service@sdccsecurity.com • www.sdccsecurity.com

Price List Effective February 1, 2017



918



728



702R



101-1AK



101-4AM