

## 15 Series Electric Strike

Distributor Discount Code **FK LIST**



- For 5/8" latch or 3/4" latch with 1/8" gap
- Choice of failsafe or failsecure
- 4.875" (124mm) radius corner
- All stainless steel parts
- 630 Satin stainless steel face plate

### SPECIFICATIONS

<b>Input</b>	200mA @ 12VDC, 150mA @ 24VDC
<b>Dimensions</b>	1-1/4" W x 4-7/8" H x 1-1/2" D

### MODEL

<b>15-4F12U</b>	Failsafe, 12VDC	<b>88.00</b>	<b>15-4S12U</b>	Failsecure, 12VDC	<b>88.00</b>
<b>15-4F24U</b>	Failsafe, 24VDC	<b>88.00</b>	<b>15-4S24U</b>	Failsecure, 24VDC	<b>88.00</b>
<b>RMB</b>	Buzzer 12/24V AC/DC operation	<b>42.00</b>	<b>BR64XL</b>	Rectifier for AC operation	<b>26.00</b>

*Not recommended for wood application*

## 25 Series Electric Strike

**LIST**



The SDC 25 Series electric strike is designed for use with locksets having 5/8" (15mm) throw latchbolt. The compact low profile design with an internally mounted solenoid and factory supplied mounting tabs enable quick and easy installation where jamb space is limited.

- For 1/2" latch or 5/8" latch with 1/8" door gap
- Latch bolt monitor standard
- Failsecure
- Field reversible for failsafe operation
- Compatible with 5/8" latchbolts
- All stainless steel parts
- 630 Stainless steel standard finish

### SPECIFICATIONS

**Dual Voltage** 200/100 mA @ 12/24VDC

**Latch Status** SPDT, 3 Amp @ 30VDC

**Dimensions** 1-1/4" W x 4-7/8" H x 1-1/2" D

### MODEL

<b>25-4U</b>	4.875" (124mm) Square corner	<b>125.00</b>
<b>RMB</b>	Buzzer 12/24V AC/DC operation	<b>40.00</b>
<b>BR64XL</b>	Rectifier for AC operation	<b>26.00</b>

*Not recommended for wood application*

## 30 Series Rim Mount Electric Strikes

Distributor Discount Code **FK**

Stainless steel electric strike for rim mount exit devices. Strike is non-handed, fail secure is standard with fail safe optional. Standard finish is stainless steel 630 (U). Check template to ensure compatibility.



30-4

SPECIFY MODEL		<input type="text"/>	<input type="text"/>	<input type="text"/>	LIST
<b>30-4-12</b>	Stainless steel electric strike designed for rim-type exit devices 12VDC@ 0.51Amp				<b>699.00</b>
<b>30-4-24</b>	Stainless steel electric strike designed for rim-type exit devices 24VDC@ 0.25Amp				<b>699.00</b>
SPECIFY FINISH		<input type="text"/>	<input type="text"/>	<input type="text"/>	Add to List
<b>U</b>	630 Dull Stainless Steel (Standard)		<b>N/C</b>		
OPTIONS		<input type="text"/>	<input type="text"/>	<input type="text"/>	Add to List
<b>FS</b>	Failsafe operation	<b>37.00</b>	<b>BR64XL</b>	Rectifier	<b>26.00</b>
<b>LCBMA-30</b>	Latch & locking cam monitor	<b>223.00</b>			

**Not Compatible with SDC S6000**  
See S6000 Electric Trim page XX