

15 Series Electric Strike

Distributor Discount Code **FK LIST**



- For 5/8" latch or 3/4" latch with 1/8" gap
- Choice of failsafe or failsecure
- 4.875" (124mm) radius corner
- All stainless steel parts
- 630 Satin stainless steel face plate

SPECIFICATIONS

Input	200mA @ 12VDC, 150mA @ 24VDC
Dimensions	1-1/4" W x 4-7/8" H x 1-1/2" D

MODEL

15-4F12U	Failsafe, 12VDC	88.00	15-4S12U	Failsecure, 12VDC	88.00
15-4F24U	Failsafe, 24VDC	88.00	15-4S24U	Failsecure, 24VDC	88.00
RMB	Buzzer 12/24V AC/DC operation	42.00	BR64XL	Rectifier for AC operation	26.00

Not recommended for wood application

25 Series Electric Strike

LIST



The SDC 25 Series electric strike is designed for use with locksets having 5/8" (15mm) throw latchbolt. The compact low profile design with an internally mounted solenoid and factory supplied mounting tabs enable quick and easy installation where jamb space is limited.

- For 1/2" latch or 5/8" latch with 1/8" door gap
- Latch bolt monitor standard
- Failsecure
- Field reversible for failsafe operation
- Compatible with 5/8" latchbolts
- All stainless steel parts
- 630 Stainless steel standard finish

SPECIFICATIONS

Dual Voltage 200/100 mA @ 12/24VDC

Latch Status SPDT, 3 Amp @ 30VDC

Dimensions 1-1/4" W x 4-7/8" H x 1-1/2" D

MODEL

25-4U	4.875" (124mm) Square corner	125.00
RMB	Buzzer 12/24V AC/DC operation	40.00
BR64XL	Rectifier for AC operation	26.00

Not recommended for wood application

30 Series Rim Mount Electric Strikes

Distributor Discount Code **FK**

Stainless steel electric strike for rim mount exit devices. Strike is non-handed, fail secure is standard with fail safe optional. Standard finish is stainless steel 630 (U). Check template to ensure compatibility.



30-4

SPECIFY MODEL		<input type="text"/>	<input type="text"/>	<input type="text"/>	LIST
30-4-12	Stainless steel electric strike designed for rim-type exit devices 12VDC@ 0.51Amp				699.00
30-4-24	Stainless steel electric strike designed for rim-type exit devices 24VDC@ 0.25Amp				699.00
SPECIFY FINISH		<input type="text"/>	<input type="text"/>	<input type="text"/>	Add to List
U	630 Dull Stainless Steel (Standard)		N/C		
OPTIONS		<input type="text"/>	<input type="text"/>	<input type="text"/>	Add to List
FS	Failsafe operation		37.00	BR64XL	Rectifier 26.00
LCBMA-30	Latch & locking cam monitor		223.00		

**Not Compatible with SDC S6000
See S6000 Electric Trim page XX**