

30 Series Electric Strike

The SDC 30-4 Series electric strike is designed for use with rim mount exit devices having pullman type latchbolts or the top pullman latch of a surface vertical-rod exit device.

FEATURES

- All stainless steel for corrosion resistance and strength
- Tamper resistant, heavy-duty construction
- Set screws for adjustment lock-down
- Milled ramps to better accommodate deadlatches
- Integrated shim for quick customization of faceplate thickness (3/4" to 1/2")
- In-frame horizontal adjustability
- Pullman keeper
- Non-handed, reversible
- Failsecure (standard) Failsafe (optional)
- 3/4" keeper depth
- Static strength 1,500 lbs.
- Dynamic strength 70 ft-lbs.



PRODUCT SKU SAMPLE: 30-4-12 U FS

HOW TO ORDER

1 | SPECIFY MODEL

30-4-12 electric strike
12VDC Electric Strike with 0.75" faceplate. Faceplate is 0.5" without 1/4" spacer

30-4-24 electric strike
24VDC Electric Strike with 0.75" faceplate. Faceplate is 0.5" without 1/4" spacer.

2 | SPECIFY FINISH

U 630 Stainless Steel (standard)

3 | SPECIFY OPTIONS

FS Failsafe operation
LBM-30 Latchbolt Monitor
LCM-30 Locking Cam Monitor
BR64XL Rectifier for AC operation

SPECIFICATIONS

Voltage	510 mA @ 12VDC 250 mA @ 24VDC
Dimensions	9" H x 1-3/4" W, 1 23/32" D

- CAN4-S104 (ULC-S104) fire door conformant
- DOD approved
- New York City accepted

