

# 30 Series Electric Strike

The SDC 30-4 Series electric strike is designed for use with rim mount exit devices having pullman type latchbolts or the top pullman latch of a surface vertical-rod exit device.

## FEATURES

- All stainless steel for corrosion resistance and strength
- Tamper resistant, heavy-duty construction
- Set screws for adjustment lock-down
- Milled ramps to better accommodate deadlatches
- Integrated shim for quick customization of faceplate thickness (3/4" to 1/2")
- In-frame horizontal adjustability
- Pullman keeper
- Non-handed, reversible
- Failsecure (standard) Failsafe (optional)
- 3/4" keeper depth
- Static strength 1,500 lbs.
- Dynamic strength 70 ft-lbs.



PRODUCT SKU SAMPLE: 30-4-12 U FS

## HOW TO ORDER

### 1 | SPECIFY MODEL

**30-4-12** electric strike  
12VDC Electric Strike with 0.75" faceplate. Faceplate is 0.5" without 1/4" spacer

**30-4-24** electric strike  
24VDC Electric Strike with 0.75" faceplate. Faceplate is 0.5" without 1/4" spacer.

### 2 | SPECIFY FINISH

**U** 630 Stainless Steel (standard)

### 3 | SPECIFY OPTIONS

**FS** Failsafe operation  
**LBM-30** Latchbolt Monitor  
**LCM-30** Locking Cam Monitor  
**BR64XL** Rectifier for AC operation

## SPECIFICATIONS

<b>Voltage</b>	510 mA @ 12VDC 250 mA @ 24VDC
<b>Dimensions</b>	9" H x 1-3/4" W, 1 23/32" D

- CAN4-S104 (ULC-S104) fire door conformant
- DOD approved
- New York City accepted

