

**410 SERIES - 1-3/4" X 1" EXIT SWITCH**      **OPTIONS - SEE PAGE 80**      **LIST**

1 3/4" x 1" Button - Green and Red Illuminated Lens included - Dull Stainless Steel finish

NOTE: AA Models Are Not Illuminated



412N  
413N  
414N

Narrow	Contact	Sign	
<b>412NU</b>	Momentary SPDT	PUSH TO EXIT	<b>76.00</b>
<b>413NU</b>	Integrated electronic timer, adj. 1-60 sec. 12/24VDC, 2A DPDT Contact	PUSH TO EXIT	<b>145.00</b>
<b>413PNU</b>	Integrated pneumatic timer, adj. 1-180 sec. 12/24VDC, SPDT 3 Amp Contact	PUSH TO EXIT	<b>342.00</b>
<b>414NU</b>	Momentary DPDT	PUSH TO EXIT	<b>91.00</b>
<b>415NU</b>	AA (On/Off) DPDT	NONE	<b>113.00</b>

**420 SERIES - 2" EXIT SWITCH**      **OPTIONS - SEE PAGE 80**      **LIST**

2" Button, Green and Red Illuminated Lens included - Dull Stainless Steel Finish

NOTE: AA Models Are Not Illuminated



422      422A  
423      423A  
424

1 Gang	Contact	Sign	
<b>422U</b>	Momentary SPDT	PUSH TO EXIT	<b>76.00</b>
<b>422AU</b>	Momentary SPDT 2" Button - Blue illuminated lens only	♿ Symbol	<b>76.00</b>
<b>423U</b>	Integrated electronic timer, adj. 1-60 sec 12/24VDC, 2A DPDT Contact	PUSH TO EXIT	<b>145.00</b>
<b>423PU</b>	Integrated pneumatic timer, adj. 1-180 sec. 12/24VDC, SPDT 3 Amp Contact	PUSH TO EXIT	<b>342.00</b>
<b>423AU</b>	Integrated 1-60 sec Timer 12/24VDC, 2A DPDT Contact 2" Button - Blue illuminated lens only	♿ Symbol	<b>145.00</b>
<b>424U</b>	Momentary DPDT	PUSH TO EXIT	<b>113.00</b>
<b>425U</b>	AA (On/Off) DPDT	NONE	<b>113.00</b>

**CODE COMPLIANT MANUAL RELEASE DEVICES**      **LIST**

Code Compliant Manual Releasing Devices and Sensors

423M and 413MN exit switches USED TOGETHER WITH the MD31D PIR sensor comply with manual releasing device and sensor device requirements for Access-Controlled Egress Doors per:

IBC International Code 1008.1.3.4    NFPA 101 7.2.1.62    BOCA National Building Code 1017.4.5  
IFC International Code 1008.1.3.4    NFPA 1 15.5.3.2    SBCCI Standard Building Code 1012.7

Code Compliant Manual Release Device

Code Compliant Features: Fixed 30 second timer, re-triggerable; Failsafe - lock releases when power to switch is interrupted; Sign - PUSH TO EXIT; CSFM Listed::

1 3/4"x1" Button, Green Illuminated Lens - Dull Stainless Steel Finish, Specify R for optional red lens



413MN      423M

Narrow	Contact	Sign	
<b>413MNU</b>	Integrated Fixed 30 sec. Timer 12/24VDC, 2 Amp Contact	PUSH TO EXIT	<b>150.00</b>

2" Button, Green Illuminated Lens - Dull Stainless Steel Finish, Specify R for optional red lens

1 Gang	Contact	Sign	
<b>423MU</b>	Integrated Fixed 30 sec. Timer 12/24VDC, 2 Amp Contact	PUSH TO EXIT	<b>150.00</b>

Code Compliant Egress Sensor

Code Compliant Features: PIR egress sensor with failsafe mode - lock releases when PIR power to PIR sensor is interrupted. UL listed 294 Access Control System Units



MD-31DOW



MD-31DB



Model	Color		
<b>MD-31DOW</b>	White	PIR Egress Sensor	<b>V 243.00</b>
<b>MD-31DB</b>	Black	PIR Egress Sensor	<b>V 243.00</b>

Input: 12 or 24 VAC/DC @ 26mA max.

Contact: 2 SPDT Dry, 2 Amp @ 30VDC (38.1 H x 148.8 W x 38.1 D mm)

Operating Temp: -20° F to 120° F (-29° C to 49° C)

Dimensions: 1.5" H x 6.25" W x 1.5" D



BB1D

**RETROFIT BACK BOX**      **LIST**

<b>BB1D</b>	Single Gang 2.25" w x 3.75" h x 2.75" D	<b>14.00</b>
-------------	---	--------------