

# 413MN and 423M Exit Switches

## Code Compliant Manual Release

### Code Compliant Manual Releasing Devices and Sensors

423M and 413MN exit switches used together with the MD31D PIR sensor comply with manual releasing device and sensor device requirements for **Access-Controlled Egress Doors** per the following codes:

- IBC International Code 1008.1.3.4
- IFC International Fire Code 1008.1.3.4
- NFPA 101 Life Safety Code 7.2.1.6.2
- NFPA 1.15.5.3.2
- BOCA National Building Code 1017.4.5
- SBCCI Standard Building Code 1012.7



423M



413MN



### FEATURES

- Fixed 30 Sec. Timer, Re-Triggerable
- Failsafe-Lock Releases when Power to Switch is Interrupted
- Green Illuminated Switch Button
- Push-to-Exit Sign
- CSFM Listed



### SPECIFICATIONS

|                       |                          |
|-----------------------|--------------------------|
| <b>Timer Contacts</b> | DPDT 2 Amp @ 12/24VDC    |
| <b>Wire Leads</b>     | 6", 20 Gauge             |
| <b>1 Gang</b>         | 2 7/8" x 4 1/2" x 20 Ga. |
| <b>Narrow</b>         | 1 3/4" x 4 1/2" x 20 Ga. |
| <b>Weight</b>         | 0.4 lbs                  |

PRODUCT SKU SAMPLE: 413MN U LT



### HOW TO ORDER

#### 1| SPECIFY MODEL



**413MN**

Narrow, Integrated Electronic Timer, Fixed 30 Sec. Timer, 1 3/4"x1" Green Illuminated Button **PUSH TO EXIT**



**423M**

1 Gang, Integrated Electronic Timer, Fixed 30 Sec. Timer, 2" Green Illuminated Button **PUSH TO EXIT**

#### 2| SPECIFY FINISHES

- U** 630 Stainless Steel - STANDARD
- C** 605 Bright Brass
- D** 606 Dull Brass
- H** 613 Oil Rubbed Bronze
- P** 625 Bright Chrome

#### 3| SPECIFY LED OPTIONS

- L1G** 1 Green LED
- L1R** 1 Red LED
- L2** 1 Red, 1 Green LED
- LT** Tri-color LED - Red, Green, Amber



