

## 480 Series Push Plate Switches - Wireless and Hardwired (continued)

Distributor Discount Code **CK LIST**

ADA Compliant



### 4 1/2" Round Push Plate Switch

- Pressing any part of the push plates 4" 1/2 active area causes switch actuation
- 1 Gang or 2 gang recessed or Surface Box Mount • Depth: SPDT 5/8" deep; DPDT 1 1/2" deep

SPDT Model Description		DPDT Model Description	
<b>48204RU</b>	Push to Open, black infill	<b>85.00</b>	<b>48404RU</b> Push to Open, black infill <b>110.00</b>
<b>482A4RU</b>	♿ Push to Open, blue infill	<b>85.00</b>	<b>484A4RU</b> ♿ Push to Open, blue infill <b>110.00</b>
<b>480-4RSB</b>	Surface box, 5" Dia., 2 1/8" O.D.	<b>56.00</b>	<b>480-4RFB</b> Black Flush Escutcheon, 5 7/8" overall diameter with trim ring <b>63.00</b>
<b>480-4RG</b>	4" round gasket	<b>15.00</b>	<b>480-4RRB</b> Surface Escutcheon, 7 7/8" Dia., 1 9/16" overall height <b>63.00</b>



### 6" Round Push Plate Switch

- Pressing any part of the push plates 6" active area causes switch actuation
- 1 Gang or 2 gang recessed or Surface Box Mount • Depth: SPDT 5/8" deep; DPDT 1 1/2" deep

SPDT Model	Description	DPDT Model	Description
<b>48206RU</b>	Push to Open, black infill	<b>90.00</b>	<b>48406RU</b> Push to Open, black infill <b>114.00</b>
<b>482A6RU</b>	♿ Push to Open, blue infill	<b>90.00</b>	<b>484A6RU</b> ♿ Push to Open, blue infill <b>114.00</b>
<b>480-6RSB</b>	Surface box Round, 6 7/16" Dia., 2 1/8" O.D.	<b>56.00</b>	<b>480-6RFB</b> Recessed Flush Escutcheon, 7 3/4" overall diameter with trim ring <b>63.00</b>
<b>480-6RG</b>	6" round gasket	<b>15.00</b>	

## 400 Series Wireless Transmitter and Receiver



Distributor Discount Code **CK LIST**

For Remote Control Versatility for Touch Panel Column and Push Plate Switches




### 433MHz Micro Transmitter

- Requires a non-metallic surface box or standard bollard cap (non-metallic). Works with 400RC433
- Pre-Wired for quick installation
- Antenna magnifies signal

**Voltage Input:** 9V Battery (included)  
**Trigger Input:** Momentary, N.O.Dry Contact  
**Temperature:** -20F — 100F  
**Dimensions:** 1-9/64" x 15/16" x 7/32" (29 x 49 x 6mm)

Model	Description	
<b>400W1-433</b>	433MHz Micro Transmitter	<b>75.00</b>



### 433MHz 1 Channel Nano Receiver

- Designed to control automatic closing and anti-burglar systems. Works with 400W1-433.

**Carrier Frequency:** 433.92 MHz  
**Relay Numbers:** 1  
**Temperature:** -4F — 158F  
**Power Supply:** 12/24 VAC/DC  
**Contacts:** C-NO  
**Dimensions:** 1-1/4" x 2" x 3/4" Deep (32 x 51 x 19mm)

Model	Description	
<b>400RC433</b>	433MHz 1 Channel Receiver	<b>88.00</b>



**SECURITY DOOR CONTROLS**  
 801 Avenida Acaso • Camarillo, CA 93012  
 Email: Service@sdcsecurity.com • www.sdcsecurity.com

Price List Effective February 1, 2017