SECURITY

BP10254



The 45F fire-rated Grade 1 strike is specially designed with a durable, stainless steel die cast body. It is engineered with corrosion resistant components with fewer moving parts for maximum life. The standard unit includes monitoring outputs, field-selectablevoltage, and field-adjustable operation (fail-secure or failsafe.) Designed for use with cylindrical and mortise locksets with 9/16" - 3/4" throw latch bolts.

- ANSI/BHMA A156.31, Grade 1
- Centerline Electric Strike
- For 9/16" or 3/4" latch with 1/8" door gap
- Latch bolt monitor standard
- Keeper closed & deadlocked standard
- Field selectable fail-secure failsafe
- Field selectable voltage 12/24V AC/DC
- 1/4" Horizontal alignment adjustment
- Static strength 1500lbs.
- Low profile, 1-3/16" deep

- All stainless steel parts with durable die cast body for corrosion resistance
- Plug-in wire connectors
- Mounting tabs
- Non-handed
- Fewer moving parts for maximum life
- 630 stainless steel standard
- UL Listed 1034 Burglary Resistant
- UL 10C, 3 Hr Fire Rated (Fail-Secure only)
- U.S. Patent #7,540,542 B2

SPECIFICATIONS





SPECIFY MODEL

MODEL

45F-4SU Included: One 4.875" square corner faceplate. Stainless steel finish standard* 399.00

List

For additional Plates contact factory

SPECIFY FINISH			Add to List			
Square Corner Faceplate						
U	630 Dull stainless Steel (std)		N/C			
Н	613 Oil Rubbed Bronze		26.00			
D	606 Dull Brass		26.00			

OPTIO	NS			Add	to List
K	Keeper open/closed status	40.00	RMB	Buzzer 12/24V AC/DC operation	42.00

