Distributor CK
Discount Code CK

### For Handicap Access, Automatic Door **Activation & Request-to-Exit Applications**

- Door Opener Activation
- Automatic Door Activation
- Access Control Request-to-Exit (RTE)
- Door Sequencer Activation




can be used with wireless = transmitter and receiver

SPECIFICA	ATIONS					
Mounting Plate	Heavy Duty 1/8" (3.2mm) mounting plate					
Faceplate	vy 18 Gauge (1.02mm), 630/US32D Satin Stainless Steel Standard					
Legends	Bold debossing or engraving with black, blue or white infill					
Contacts	SPDT or DPDT, 15 Amps @ 125/250VAC; UL 1054, CSA Listed					
Depth	[Narrow & (1) Gang] SPDT-7/8" deep, DPDT-1-3/8" deep, [4 ½", & 6" square/ round] SPDT-3/4" deep, DPDT-1-5/32					

















# 2¾" x 4½" Single (1) Gang Push Plate Switch

- Pressing any part of the push plate (2 3/4" x 4 1/2") causes switch actuation
- Recessed, Surface Box or Bollard Mount Depth: SPDT 3/4" deep; DPDT 1 1/2" deep

			•	· ·	
SPDT Model	Description		DPDT Model	Description	
482O2U	Push to Open, black infill	77.00	484O2U	Push to Open, black infill	102.00
482A2U	5 Push to Open, blue infill	77.00	484A2U	5. Push to Open, blue infill	102.00
480-2SB	Surface mount box, 2 3/4" x 4	4 1/2" x 1 5	5/8" O.D.		29.00
















- Pressing any part of the push plates 4" ½" x 4 ½" active area causes switch actuation
- 1 Gang or 2 gang recessed or Surface Box Mount Depth: SPDT 5/8" deep; DPDT 1 1/2" deep

SPDT Model	Description		DPDT Model	Description	
482O4U	Push to Open, black infill	85.00	484O4U	Push to Open, black infil	110.00
482A4U	5 Push to Open, blue infill	85.00	484A4U	5 Push to Open, blue infill	110.00
480-4FB	Square Flush Recessed box, 1-gang, 6 3/4" x 6 3/4" x 1 7/8" O.D.				63.00
480-4SBB	Surface mount box, 4-1/2" x 4-1/2" x 1 3/4" O.D. with Battery compartment for wireless				33.00
480-4SB	Surface mount box, 4-1/2" x 4-1/2" x 1 7/8" O.D.				63.00
480-4SE	3-sided stainless shrout for e	exterior app	lications, 4-11/1	6" x 4-7/8" x 12"	38.00







## 6" x 6" Square Push Plate Switch

- Pressing any part of the push plates 6" x 6" active area causes switch actuation
- 1 Gang or 2 gang recessed or Surface Box Mount Depth: SPDT %" deep; DPDT 1 ½" deep

SPDT Model	Description		DPDT Model	Description	
48206U	Push to Open, black infil	90.00	484O6U	Push to Open, black infil	114.00
482A6U	& Push to Open, blue infill	90.00	484A6U	5. Push to Open, blue infill	114.00
480-6SBB	Surface mount box, 2-gang	Battery C	ompartment, 4 1/	/2" x 4 1/2" x 1 3/4" O.D.	33.00


# 480 Series Push Plate Switches - Wireless and Hardwired (continued)











Pressing any part of the push plates 4" ½ active area causes switch actuation

1 Gang or 2 gang recessed or Surface Box Mount • Depth: SPDT %" deep; DPDT 1 1/2" deep

SPDT Model Description			DPDT Model Description		
482O4RU	Push to Open, black infil	85.00	48404RU	Push to Open, black infil	110.00
482A4RU	Push to Open, blue infill	85.00	484A4RU	Push to Open, blue infill	110.00
480-4RSB	Surface box, 5" Dia., 2 1/8" O.D.	56.00	480-4RFB	Black Flush Escutcheon, 5 7/8" overall diameter with trim ring	63.00
480-4RG	4" round gasket	15.00	480-4RRB	Surface Escutcheon, 7 7/8" Dia., 1 9/16" overall height	63.00





#### 6" Round Push Plate Switch

Pressing any part of the push plates 6" active area causes switch actuation

1 Gang or 2 gang recessed or Surface Box Mount 

Depth: SPDT %" deep; DPDT 1 ½" deep

SPDT Model	Description		DPDT Model	Description	
48206RU	Push to Open, black infil	90.00	48406RU	Push to Open, black infil	114.00
482A6RU	& Push to Open, blue infill	90.00	484A6RU	& Push to Open, blue infill	114.00
480-6RSB	Surface box Round, 6 7/16" Dia., 2 1/8" O.D.	56.00	480-6RFB	Recessed Flush Escutcheon, 7 3/4" overall diameter with trim ring	63.00
480-6RG	6" round gasket	15.00			

# 480 Series Touch Panel Column - Wireless & Hardwire

Distributor CK
Discount Code

# **Applications**

- Wireless & Hardwire
- ADA Ingress/R.E.X/Egress Door Opener Activation
- Access Control Request-to-Exit (REX)
- **Door Opener Activation**

**SPDT Model** 

482AA9

- Automatic Door Activation or Lock Release
- Automatic Door & Exit Device Sequencer Activation



can be used with wireless transmitter and receiver

## **Features**

- Surface wall mount or bollard mount
- Sleek Architectural profile
- No square edges to snag, wide sloping sides deflects impact movement naturally to activate column
- Deflects impact from wheeled carts and conveyances
- Impact & Vandal resistant design, inhibits prying, tampering
- Weather Resistant, no gaps for water or ice penetration
- Choice of SPDT or DPDT, 15 Amps @ 125/250VAC


# 9" X 6" INGRESS-R.E.X TOUCH PANEL COLUMN

Description

5. Push to Open

List

292.00



Fully Active 90 Sq. Inch Actuation Area

Recommended mounting height is 3" from floor

Material: Sturdy 1/8" extrusion with architectural finish **Overall Size:** 9" h x 6" w x 1-1/2" d (229 x 152 x 38mm) Active Area: 9" h x 2-1/2" w (229 x 63.5mm)



SPECIFY FINISH			Add to List
V 628 Aluminum (standard), blue infill	N/C	X 613 Dark Bronze, white infill	24.00

List

# 36" X 6" INGRESS-R.E.X TOUCH PANEL COLUMN

Material: Sturdy 1/8" extrusion with architectural finish **Overall Size:** 36" h x 6" w x 1-1/2" d (914 x 152 x 38mm)

Active Area: 36" h x 2-1/2" w (914 x 63.5mm)

SPDT Model Description **DPDT Model** Description 430.00 482AA36 5 Push to Open 404.00 484AA36 5 Push to Open

SPECIFY FINISH Add to List

V 628 Aluminum (standard), blue infill X 613 Dark Bronze, white infill N/C

