add to list

7500 Series HiTower®

HiTower® - Electric Frame Actuator Controlled Locksets

The HiTower utilizes SDC's original concept of utilizing an electric frame actuator to control a mechanical lock in the door, eliminating the cost and labor associated with a power transfer hinge and wires through the door.

MEA City of New York





Distributor LK Discount Code

HiTower® Z7500

- SDC brand Grade 1 Heavy Duty lockset
- Field selectable function,

Locked outside only or both sides

HiTower® CONVERSIONS

Distributors provide a new mechanical lock brand of choice to the factory for conversion to an electric frame actuator controlled lockset.

շ(ՍԼ)

Electrically Controlled Single Point Locks or Latches 3 Hr A Label Fire Rated Doors



SPECIFY SOURCE OF MORTISE LOCK

HiTower® Pro - SDC supplied mortise lock and electric frame actuator, complete with lever trim (Cylinder not included)

ZR SDC Retrofit lockset, replaces discontinued 5000/6000 series Z SDC lockset

ZY SDC retrofit lockset replaces SDC modifications of discontinued manufacturer models: Falcon-LM581; Sargent-7704/7705; Corbin-9557L/2257; Russwin- 7059L; Arrow-1600EW; Yale-8705; Almet-5007; Best-35HEW

HiTower® Mod - SDC supplied Schlage mortise lock and electric frame actuator, less lever trim

ZS Schlage L9080

HiTower® Mod - Distributors supply SDC with the mortise lock body and armored front (less trim) for modification. SDC returns the modified lock body with an electric actuator. Upon installation, two lever return spring cages (supplied by distributor) are required for proper operation.



	A	Falcon*	LM-561/MA581	Р	Yale	8805
ı	D	Sargent	8204	R	Schlage Retro	L9080 (replaces 5000 series)
	Н	Hager	3880	s	Schlage	L9080
	ı	Corbin/Russwin	2057	Т	Best	35 HEW and 45H
	N	Arrow	B12	U	Dorma	M9000
ı	0	Yale	7130F-L5 Exit device	٧	Marks	5EW
			*ΔII F	alcon	locks must be supplied wit	h 0201000-000 face plate, less hub locking har



SPECIFY HAND L Left hand

SPECIFY FINISH

R Right hand

7530 Locked both sides. Unlocked by access control, remote control and key from either side, failsafe

Locked outside only. Unlocked by access control, remote control, outside key and inside lever, failsafe 7550

Locked both sides. Unlocked by access control, remote control and key from either side, failsecure

Locked outside only. Unlocked by access control, remote control, outside key and inside lever, failsecure 7570

Left hand reversed

Right hand reversed





O7550

Yale Conversion





	0	
	1	
,	07F	

ACTUATOR VOLTAGE AND	FRAME SIZE		
ailsafe actuator for -3/4" to 2" face frames	Extra Na for 1-1/4'	 	

A	CTUATOR VOLTAGE AND FRAM	ME S	SIZE	_	see page 35 for pricing	
Failsafe actuator for 1-3/4" to 2" face frames			tra Narrow failsafe actuator 1-1/4" to 1-1/2" face frames	+Failsecure actuator for 2" face frames		
Α	115VAC 0.2 Amps	D	115VAC 0.2 Amps	G	115VAC 0.2 Amps	
В	24VAC 0.5 Amps	Е	24VAC 0.5 Amps	Н	24VAC 0.5 Amps	
С	24VDC 0.5 Amps	F	24VDC 0.5 Amps	J	24VDC 0.5 Amps	

+ Fail Secure Actuator Available with Z or S lockset only. Special strike preparation required for S7560/7570

LR

RR

	Q 626 Dull Chrome (standard)									
	C 605 Bright Brass	52.00	G 612	Dull Bronze	52.00	s	629 Bright Stainless Steel	52.00		
}	D 606 Dull Brass	52.00	H 613	Oil Rubbed Bronze	52.00	U	630 Dull Stainless Steel	52.00		
	F 611 Bright Bronze	52.00	P 625	Bright Chrome	52.00					
	SPECIFY LEVER TRIM FO	R Z, ZR 8	k ZY			Ι	ado	d to list		

SPECIFY LEVER TRIM FOR Z, ZR & ZY			add to list
G Galaxy with rose	N/C	GE Galaxy with escutcheon	104.00
E Eclipse with rose	N/C	EE Eclipse with escutcheon	104.00
N Nova with rose	N/C	NE Nova with escutcheon	104.00
07 Schlage style with SDC B rose	N/C	07E Schlage style with SDC escutcheon	104.00

		PRICING E	istributor unt Code LK	LIST							
l	HiTower [®] PRO	Sources Z,				m, mortise lock and electric frame actuator. nd 12 POA, consult factory for minimum qty.					
		SOURCE/FUNCTION									
		Z7530	SDC F	Failsafe, loc	ked both side	es with rose trim	730.0	00			
		Z7550	SDC F	Failsafe, loc	ked outside o	only with rose trim	720.0	00			
		Z7560	SDC F	Failsecure, l	ocked Both s	sides with rose trim	885.0	00			
		Z7570	SDC F	Failsecure, l	ocked outside	e only with rose trim	875.0	00			
		ZY7530	,	(Replaces d Failsafe, loc	730.0	00					
		ZY7550	,	(Replaces d Failsafe, locl	720.0	00					
		ZR7530	SDC ((Replaces 5	000 series) Fa	ailsafe, locked both sides with rose trim	834.0	00			
		ZR7550	SDC ((Replaces 5	000 series) Fa	ailsafe, locked outside only with rose trim	823.0	00			
		ZR7560	SDC ((Replaces 6	000 series) Fa	ailsecure, locked both sides with rose trim	885.0	00			
		ZR7570	SDC ((Replaces 6	000 series) Fa	ailsecure, locked outside only with rose trim	875.0	00			
		(Actuator type	Extra Narrow Failsafe Frame Actuator (Actuator type D, E, F, only page XX) For 1-1/4" to 1-1/2" frames. Special strike prep required. Not available with ZR or failsecure 7560 and 7570								
		Rose Trim					N/	'C			
		Escutcheo	on trim				Add 104.0	00			
ı	HiTower [®] MOD	Source ZS (see previous page). Special order, no returns, no cancellation SDC supplied - Schlage L mortise lock and electric frame actuator, less lever trim SOURCE/FUNCTION									
		ZS7530	Schlage F	ailsafe, lock	ked both sides	s	PC)A			
		ZS7530 ZS7550			ked both sides ked outside or		PC PC				
	HiTower [®] MOD	ZS7550 Sources A, Distributor su	Schlage F	S, T (see pr	revious page)	nly	PC				
	HiTower [®] MOD	Sources A, Distributor su SOURCE/FU	Schlage F. D, I, N, O, P, upplied - Majo	S, T (see proper brand me	revious page)	nly for modification, SDC supplied Electric frame	PC actuator	DA			
-	HiTower [⊚] MOD	Sources A, Distributor st SOURCE/FUI A, D, H, I, N	Schlage F D, I, N, O, P, upplied - Majo	S, T (see proper brand me	revious page) chanical lock Failsafe, loc	for modification, SDC supplied Electric frame	PC	DA 00			
	HiTower [®] MOD	Sources A, Distributor st SOURCE/FUI A, D, H, I, N	Schlage F D, I, N, O, P, upplied - Majo	S, T (see proper brand me	revious page) chanical lock Failsafe, loc Failsafe, loc	for modification, SDC supplied Electric frame cked both sides cked outside only	PC e actuator 497.0	DA			
	HiTower [®] MOD	Sources A, Distributor so SOURCE/FU A, D, H, I, N A, D, H, I, N	Schlage F D, I, N, O, P, upplied - Majo	S, T (see proper brand me	revious page) chanical lock Failsafe, loc Failsafe, loc Failsecure,	for modification, SDC supplied Electric frame	PC actuator	DA			
	HiTower [®] MOD	Sources A, Distributor st SOURCE/FU A, D, H, I, N A, D, H, I, N S7560 S7570 Extra Narro	Schlage F D, I, N, O, P, upplied - Majo INCTION N, P, S, T, U, N N, O, P, S, T, U	S, T (see proper brand me V 7530 U, V 7550	revious page) schanical lock Failsafe, loc Failsafe, loc Failsecure, Failsecure,	for modification, SDC supplied Electric frame cked both sides cked outside only locked both sides (5.75" Strike plate)	PC e actuator 497.0 461.0 647.0	DA			
	HiTower [®] MOD	ZS7550 Sources A, Distributor st SOURCE/FU A, D, H, I, N A, D, H, I, N S7560 S7570 Extra Narro (Actuator typ	Schlage F D, I, N, O, P, upplied - Majo INCTION N, P, S, T, U, N N, O, P, S, T, U	S, T (see proper brand me V 7530 U, V 7550 Frame Actur Page XX) F	revious page) chanical lock Failsafe, loc Failsaecure, Failsecure, Tailsecure, Failsecure, Tailsecure, Tailsecure	for modification, SDC supplied Electric frame cked both sides cked outside only locked both sides (5.75" Strike plate) locked outside only (5.75" Strike plate)	PC e actuator 497.0 461.0 647.0	DA			
	HiTower® MOD	ZS7550 Sources A, Distributor st SOURCE/FUI A, D, H, I, N A, D, H, I, N S7560 S7570 Extra Narro (Actuator typ Not available Source R (s	Schlage F D, I, N, O, P, pupplied - Major INCTION N, P, S, T, U, N N, O, P, S, T, U OW Failsafe F De D, E, F only e with failsecur see previous pa	S, T (see proportion of the pr	revious page) chanical lock Failsafe, loc Failsafe, loc Failsecure, Failsecure, for 1-1/4" to 1-	for modification, SDC supplied Electric frame cked both sides cked outside only locked both sides (5.75" Strike plate) locked outside only (5.75" Strike plate)	497.0 461.0 647.0 125.0	DA			
		ZS7550 Sources A, Distributor st SOURCE/FUI A, D, H, I, N A, D, H, I, N S7560 S7570 Extra Narro (Actuator typ Not available Source R (s	Schlage F D, I, N, O, P, supplied - Major INCTION N, P, S, T, U, V N, O, P, S, T, U OW Failsafe F De D, E, F only e with failsecur see previous paupplied - Schlage gupplied - Schlage Schlage F De D, E, F only E with failsecur	S, T (see proportion of the pr	revious page) chanical lock Failsafe, loc Failsafe, loc Failsecure, Failsecure, for 1-1/4" to 1-	for modification, SDC supplied Electric frame cked both sides cked outside only locked both sides (5.75" Strike plate) locked outside only (5.75" Strike plate) 1/2" frames. Special strike prep required.	497.0 461.0 647.0 125.0	DA			
		ZS7550 Sources A, Distributor st SOURCE/FU A, D, H, I, N A, D, H, I, N S7560 S7570 Extra Narro (Actuator typ Not available Source R (s Distributor st	Schlage F D, I, N, O, P, upplied - Major INCTION N, P, S, T, U, N N, O, P, S, T, U ow Failsafe F pe D, E, F only e with failsecur see previous pr upplied - Schla	S, T (see proper brand me V 7530 U, V 7550 Frame Acture page XX) Free 7560 and page) lage L9080	revious page) schanical lock Failsafe, loc Failsafe, loc Failsecure, Failsecure, Tailsecure, Tailsecur	for modification, SDC supplied Electric frame cked both sides cked outside only locked both sides (5.75" Strike plate) locked outside only (5.75" Strike plate) 1/2" frames. Special strike prep required.	497.0 461.0 647.0 125.0	00 00 00 00 00			
		ZS7550 Sources A, Distributor so SOURCE/FU A, D, H, I, N A, D, H, I, N S7560 S7570 Extra Narro (Actuator typ Not available Source R (s Distributor so SOURCE/FU	Schlage F D, I, N, O, P, Rupplied - Major INCTION N, P, S, T, U, V N, O, P, S, T, U OW Failsafe F De D, E, F only We with failsecur See previous parapplied - Schla INCTION (Replaces 5)	S, T (see proper brand me problem) 7530 U, V 7530 U, V 7550 Frame Acture page XX) Free 7560 and page) lage L9080 (series)	revious page) chanical lock Failsafe, loc Failsecure, Failsecure, ator for 1-1/4" to 1-	for modification, SDC supplied Electric frame cked both sides cked outside only locked both sides (5.75" Strike plate) locked outside only (5.75" Strike plate) 1/2" frames. Special strike prep required.	497.0 461.0 647.0 125.0	00 00 00 00 00			
Н		ZS7550 Sources A, Distributor st SOURCE/FU A, D, H, I, N A, D, H, I, N S7560 S7570 Extra Narro (Actuator typ Not available Source R (s Distributor st SOURCE/FU R7530 R7550 ORIES	Schlage F D, I, N, O, P, Rupplied - Major INCTION N, P, S, T, U, V N, O, P, S, T, U OW Failsafe F De D, E, F only We with failsecur See previous parapplied - Schla INCTION (Replaces 5)	S, T (see proper brand me problem) 7530 U, V 7530 U, V 7550 Frame Acture page XX) Free 7560 and page) lage L9080 (series)	revious page) chanical lock Failsafe, loc Failsecure, Failsecure, ator for 1-1/4" to 1-	for modification, SDC supplied Electric frame cked both sides cked outside only locked both sides (5.75" Strike plate) locked outside only (5.75" Strike plate) 1/2" frames. Special strike prep required.	497.0 461.0 647.0 125.0	DA			
Н	iTower® MOD NS AND ACCESSO atus and wire har Latch status s	ZS7550 Sources A, Distributor so SOURCE/FU A, D, H, I, N A, D, H, I, N S7560 S7570 Extra Narro (Actuator typ Not available Source R (s Distributor so SOURCE/FU R7530 R7550 ORIES	Schlage F. D, I, N, O, P, pupplied - Major INCTION N, P, S, T, U, N N, O, P, S, T, U ow Failsafe F pe D, E, F only e with failsecur see previous par pupplied - Schla INCTION (Replaces 5 C Amps	S, T (see proper brand me prop	revious page) schanical lock Failsafe, loc Failsecure, Failsecure, Failsecure, Tor 1-1/4" to 1-1/47570 The chanical lock Failsafe, lock Failsafe, lock Failsafe, lock Failsafe, lock Failsafe, lock Failsafe, lock	for modification, SDC supplied Electric frame cked both sides cked outside only locked both sides (5.75" Strike plate) locked outside only (5.75" Strike plate) 1/2" frames. Special strike prep required.	497.0 461.0 647.0 125.0 125.0 126.0 127.0 128.0	00 00 00 00 00 00 00 00 00 List			
OPTIOI Lock st	iTower [®] MOD NS AND ACCESSO atus and wire har	ZS7550 Sources A, Distributor st SOURCE/FU A, D, H, I, N A, D, H, I, N S7560 S7570 Extra Narro (Actuator typ Not available Source R (s Distributor st SOURCE/FU R7530 R7550 ORIES Thess witch, SPDT, 5	Schlage F D, I, N, O, P, supplied - Major Inction N, P, S, T, U, N, N, O, P, S, T, U, N, O, P, S, T,	Frame Acture page L9080 lage L9080 series)	revious page) schanical lock Failsafe, loc Failsecure, Failsecure, Failsecure, Tor 1-1/4" to 1-1/47570 The chanical lock Failsafe, lock Failsafe, lock Failsafe, lock Failsafe, lock Failsafe, lock Failsafe, lock	for modification, SDC supplied Electric frame cked both sides cked outside only locked both sides (5.75" Strike plate) locked outside only (5.75" Strike plate) 1/2" frames. Special strike prep required. cked both sides ked both sides ked outside only	497.0 461.0 647.0 637.0 125.0 me actuator 549.1 Add to	00 00 00 00 00 00 00 00 00 List			

L	Latch status switch, SPDT, 5 Amps @ 30VDC	63.00				
s	Latch and deadlock status, 3 Amps @ 30VDC	104.00				
SC-10	Socket connectors with 10 ft. cable, power wiring only	63.00				
SC-10-5	Socket connectors with 10 ft. cable for power and options	80.00				
Special Strikes						

7500EB-S	For standard actuator in 1-3/4" or 2" face frame	32.00
7500EB-N	For narrow actuator in 1-1/4" or 1-1/2" face frame	32.00

Optional Key Cylinders

CYL-6KDQ 6 pin, 1.125" keyed different, 626 Dull Chrome CYL-6KAQ 6 pin, 1.125" keyed alike, 626 Dull Chrome



32.00 32.00

35

SSP Special retrofit strike plate

125.00

Specify extended lip strike in writing