

PRICING BY SOURCE AND FUNCTION

Distributor Discount Code LK LIST

HiTower® PRO

Sources Z, ZR, ZY: SDC supplied - SDC lever trim, mortise lock and electric frame actuator. Schlage style lever trim 07 and 12 POA, consult factory for minimum qty.

SOURCE/FUNCTION

| | | | |
|---|------------|---|-------------------|
| Z7530 | SDC | Failsafe, locked both sides with rose trim | 730.00 |
| Z7550 | SDC | Failsafe, locked outside only with rose trim | 720.00 |
| Z7560 | SDC | Failsecure, locked Both sides with rose trim | 885.00 |
| Z7570 | SDC | Failsecure, locked outside only with rose trim | 875.00 |
| ZY7530 | SDC | (Replaces discontinued lock models, see 21 for details) Failsafe, locked both sides with rose trim | 730.00 |
| ZY7550 | SDC | (Replaces discontinued lock models, see 21 for details) Failsafe, locked outside only with rose trim | 720.00 |
| ZR7530 | SDC | (Replaces 5000 series) Failsafe, locked both sides with rose trim | 834.00 |
| ZR7550 | SDC | (Replaces 5000 series) Failsafe, locked outside only with rose trim | 823.00 |
| ZR7560 | SDC | (Replaces 6000 series) Failsecure, locked both sides with rose trim | 885.00 |
| ZR7570 | SDC | (Replaces 6000 series) Failsecure, locked outside only with rose trim | 875.00 |
| Extra Narrow Failsafe Frame Actuator | | | Add 125.00 |
| (Actuator type D, E, F, only page XX) For 1-1/4" to 1-1/2" frames. Special strike prep required. Not available with ZR or failsecure 7560 and 7570 | | | |
| Rose Trim | | | N/C |
| Escutcheon trim | | | Add 104.00 |

HiTower® MOD

Source ZS (see previous page). **Special order, no returns, no cancellation**
SDC supplied - Schlage L mortise lock and electric frame actuator, **less lever trim**

SOURCE/FUNCTION

| | | | |
|---------------|----------------|-------------------------------|------------|
| ZS7530 | Schlage | Failsafe, locked both sides | POA |
| ZS7550 | Schlage | Failsafe, locked outside only | POA |

HiTower® MOD

Sources A, D, I, N, O, P, S, T (see previous page)
Distributor supplied - Major brand mechanical lock for modification, SDC supplied Electric frame actuator

SOURCE/FUNCTION

| | | |
|--|--|---------------|
| A, D, H, I, N, P, S, T, U, V 7530 | Failsafe, locked both sides | 497.00 |
| A, D, H, I, N, O, P, S, T, U, V 7550 | Failsafe, locked outside only | 461.00 |
| S7560 | Failsecure, locked both sides (5.75" Strike plate) | 647.00 |
| S7570 | Failsecure, locked outside only (5.75" Strike plate) | 637.00 |
| Extra Narrow Failsafe Frame Actuator | | 125.00 |
| (Actuator type D, E, F only page XX) For 1-1/4" to 1-1/2" frames. Special strike prep required. Not available with failsecure 7560 and 7570 | | |

HiTower® MOD

Source R (see previous page)
Distributor supplied - Schlage L9080 mechanical lock for modification. SDC supplied Electric frame actuator

SOURCE/FUNCTION

| | | |
|--------------|--|---------------|
| R7530 | (Replaces 5000 series) Failsafe, locked both sides | 549.00 |
| R7550 | (Replaces 5000 series) Failsafe, locked outside only | 518.00 |

OPTIONS AND ACCESSORIES

Add to List

Lock status and wire harness

| | | |
|----------------|---|---------------|
| L | Latch status switch, SPDT, 5 Amps @ 30VDC | 63.00 |
| S | Latch and deadlock status, 3 Amps @ 30VDC | 104.00 |
| SC-10 | Socket connectors with 10 ft. cable, power wiring only | 63.00 |
| SC-10-5 | Socket connectors with 10 ft. cable for power and options | 80.00 |

Electrical back boxes for frame actuators with conduit knockouts:
(Recommended for new construction)

| | | |
|-----------------|--|--------------|
| 7500EB-S | For standard actuator in 1-3/4" or 2" face frame | 32.00 |
| 7500EB-N | For narrow actuator in 1-1/4" or 1-1/2" face frame | 32.00 |

Optional Key Cylinders

| | | |
|------------------|--|--------------|
| CYL-6KDDQ | 6 pin, 1.125" keyed different, 626 Dull Chrome | 32.00 |
| CYL-6KAQ | 6 pin, 1.125" keyed alike, 626 Dull Chrome | 32.00 |



Special Strikes

| | | |
|------------|-------------------------------|---------------|
| SSP | Special retrofit strike plate | 125.00 |
|------------|-------------------------------|---------------|

Specify extended lip strike in writing

POA

