

SELECTRIC™ PRO Z7800 Electric Lockset



Distributor Discount Code **LSK**

SELECTRIC® Pro Locksets incorporate an SDC manufactured Grade 1 Heavy Duty mortise lockset and vandal resistant clutch mechanism. Proprietary to SDC, SELECTRIC® Pro locksets. All operational attributes are field selectable. In addition, SELECTRIC® Pro locksets retrofit many other mechanical lock brands making them fully compatible with new and retrofit applications.

FIELD SELECTABLE ATTRIBUTES


- Selectable mode, failsafe or failsecure
- Selectable function, locked outside only or both sides
- Selectable voltage, 12 or 24VDC
- Selectable handing



Electrically Controlled
Single Point Locks or
Latches
3 Hr A Label Fire
Rated Doors



3773-0324-104



SPECIFY FUNCTION AND MODE

LIST

SDC Supplied Electrified Lock (Mortise cylinder not included). SDC Brand 7800 lockset. Clutch for lever trim vandal resistance. * Less trim - compatible with Schlage trim

		* Less Trim	With SDC Trim
Z7830	Locked both sides, failsafe. Field reversible to failsecure mode.	306.00	735.00
Z7850	Locked outside only, failsafe. Field reversible to failsecure mode.	306.00	735.00
Z7832	Locked both sides, failsecure. Field reversible to failsafe mode.	306.00	735.00
Z7852	Locked outside only, failsecure. Field reversible to failsafe mode.	306.00	735.00
Z7835	Locked outside and/or inside. Outside failsecure, inside failsafe	466.00	849.00

VOLTAGE - Z7835 ONLY

Specify voltage for Z7835 function only. Leave blank for all other functions which are 12/24VDC, field selectable

12 12VDC	24 24VDC	N/C

SPECIFY HAND

L Left hand	LR Left hand reversed	All hands are field reversible	N/C
R Right hand	RR Right hand reversed	without disassembly (exception Z7835)	N/C

SPECIFY FINISH

Add to List

Q 626 Dull Chrome (standard)	N/C		
C 605 Bright Brass	52.00	G 612 Dull Bronze	52.00
D 606 Dull Brass	52.00	H 613 Oil Rubbed Bronze	52.00
F 611 Bright Bronze	52.00	U 630 Dull Stainless Steel	52.00
		S 629 Bright Stainless Steel	52.00
		P 625 Bright Chrome	52.00

SPECIFY LEVER TRIM

Add to List

G Galaxy with rose	N/C	GE Galaxy with escutcheon	104.00
E Eclipse with rose	N/C	EE Eclipse with escutcheon	104.00
N Nova with rose	N/C	NE Nova with escutcheon	104.00
07 Schlage equal with SDC B rose	N/C	07E Schlage equal with SDC escutcheon	104.00

OPTIONS AND ACCESSORIES

Add to List

Optional Outputs

R Request-to-exit. Indicates inside lever operation for access control request-to-exit input, alarm shunt, remote annunciation or CCTV activation, SPDT 5 Amp @ 30VDC	83.00
D Door position status output. Indicates door open and door closed. SPDT 5 Amp @ 30VDC.	83.00
S Latched & locked status output. Indicates door latched and locked and door unlocked. SPDT 5 Amp @ 30VDC	104.00

Optional Cable and Connectors

CC1-5 5ft. Cable and connectors for locks without optional outputs	47.00
CC3-5 5ft. Cable and connectors for locks with optional outputs	63.00

Optional Key Cylinders



1 required for 7850/7852 2 required for 7830/7832 **32.00**

CYL-6KDK 6 pin, 1.125" keyed different, 626 Dull Chrome	32.00
CYL-6KAQ 6 pin, 1.125" keyed alike, 626 Dull Chrome	32.00

Power Transfer Hinge

UL listed, 4.5", five knuckle hinge. Special finish available

PTH-4Q Four wire, dull chrome	156.00
PTH-10Q Ten wire, dull chrome	202.00
PTH-2+4Q 6-wire Electric Hinge 1-pair 16 Amp inrush, 4 Amp continuous;2-pair 1 Amp @ 12/24V	182.00



PTH
UL 10B Listed for 3Hr
Fire Rated Doors
See page XX

Price List Effective February 1, 2017

SECURITY DOOR CONTROLS
801 Avenida Acaso • Camarillo, CA 93012
Email: Service@sdsecurity.com • www.sdsecurity.com



Electrified Locksets