



918



500 user codes, 1 to 6 digits in length, 4 outputs, 2 relay and 2 solid state outputs timed or latching (on/off). Assign entry PIN's to relays 1 and/or 2. Tactile keys with selectable audible volume for key depression or output activation. LED Status: Access, lockout. Timed anti-passback. Keypad tamper lockout. Request-to-Exit/Enter input. Indoor blue backlit, moisture resistant keypad. Thick S.S. faceplate 3/32" (2mm).

**ELECTRICAL SPECIFICATIONS**

<b>Voltage</b>	12/24 VAC/DC — 5-16 VDC for Wiegand
<b>Current</b>	30mA typical, 150mA maximum - 60mA max for Wiegand
<b>Outputs (918)</b>	Relay 1 - SPDT 5 Amps @ 30VDC, Relay 2 - SPDT 2 Amps @ 30VDC, Switch to Common Outputs 3 & 4 - 100mA @ 30VDC
<b>Dimensions</b>	3"W x 4-3/4"H x 1-1/2"D (1/4" Wall projection)



918W



- 918** Stand alone digital indoor keypad **166.00**
- 918W** Indoor digital keypad, Wiegand output **166.00**

**SPECIFY FINISH** Add to List

<b>U</b>	630 Brushed Stainless Steel (standard)	<b>N/C</b>	<b>H</b>	613 Oil Rubbed Bronze	<b>63.00</b>
<b>C</b>	605 Bright Brass	<b>63.00</b>	<b>P</b>	625 Bright Chrome	<b>63.00</b>
<b>D</b>	606 Dull Brass	<b>63.00</b>			

**OPTIONS** Add to List

- TR12** Plug in power supply (optional) **75.00**  
120 VAC primary, Output: 12VDC @ 1Amp, Secondary screw terminals with ground terminal

**ACCESSORIES** Add to List

- 900-PS** Privacy & Rain Shroud for stand alone digital keypads 918. Ensure protection from rain and security from spying eyes. **100.00**



900-PS with 918 Keypad

