

Auto EntryControl™

Distributor Discount Code **XK**

Auto EntryControl's™ non-pivot drive and combination of belt, gear and pulley requires less torque, requires less power, absorbs more abuse, and is quieter than other automatic door openers while complying with all US and Canadian ADA requirements. On-board diagnostics simplifies troubleshooting for ease of installation and all Auto EntryControl's™ can be easily configured for surface mounted push/pull or overhead concealed applications.

- ADA Compliant
- Complies with ANSI A 156.19
- UL - Certified for use as fire door operators (3 hour rating)
- Self-Tuning, Self-Learning
- Minimum 5 seconds from close to open
- Stays open for 5 seconds
- 130 degree of opening
- Push or Pull (In door, Out swing)
- Activation: Knowing Act
- Optional Safety Device
- Input Power: 1A, 100W
- Non-Handed
- Extremely Quiet Operation



ADA Compliant

Price List Effective February 1, 2017

SINGLE DOOR OPENING

SPECIFY MODEL LIST

Model	Description	
AUTO	Auto EntryControl™ Single Swing Door Operator	2270.00

OPERATION Add to List

Operation	Description	
1	PUSH arm plus standard spindle	N/C
2	PULL arm plus standard spindle	N/C
3	One PUSH arm plus spindle, one PULL arm plus spindle	270.00

DOOR OPENING Add to

Width	Description	
36	for 36" Door Opening	N/C
42	for 42" Door Opening	N/C
48	for 48" Door Opening	N/C

COLOR Add to List

Color	Description	
V	Aluminum	N/C
X	Dark Bronze Powder Coat	POA

DOUBLE DOOR OPENING (SPECIAL ORDER)

SPECIFY MODEL LIST

Model	Description	
AUTO	Auto EntryControl™ Double Swing Door Operator	4599.00

OPERATION Add to List

Operation	Description	
1	Two PUSH arm plus standard spindle	N/C
2	Two PULL arm plus standard spindle	N/C
3	One PULL arm plus spindle, one DOUBLE EGRESS arm plus spindle	401.00

DOOR OPENING Add to List

Width	Description	
72	for 72" Double Door opening	N/C
84	for 84" Double Door opening	N/C
96	for 96" Double Door opening	N/C

COLOR Add to List

Color	Description	
V	Aluminum	N/C
X	Dark Bronze Powder Coat	POA

ACCESSORIES

Distributor Discount Code **V LIST**

AUTO-IR36	Door-mounted Presence Sensor and Door Re-Activator - 36 inches	340.00
AUTO-IR48	Door-mounted Presence Sensor and Door Re-Activator - 48 inches	360.00

OPTIONAL ARM EXTENSIONS FOR REVEAL GREATER THAN 8 INCHES List

AUTO-AEV	Arm Extension for PUSH arm - Aluminum	100.00
AUTO-AEX	Arm Extension for PUSH arm - Dark Bronze Powder Coat	140.00

OPTIONAL SPINDLES List

SP20	20mm Spindle	75.00
SP35	35mm Spindle	75.00
SP50	50mm Spindle	75.00
SP80	80mm Spindle	90.00



SECURITY DOOR CONTROLS
801 Avenida Acaso • Camarillo, CA 93012
Email: Service@sdsecurity.com • www.sdsecurity.com



Dual Switch Bollard Post - CBC compliant

Distributor Discount Code **CK**



NEW

- California CBC Section 11B 404.3 code compliant bollard and switch plates
- Black HDPE mortised removable cap with secure transmitter mount
- Two 4-1/2" ♿ Push to Open blue infill push plates, located at 7" and 36" centerline from floor
- 6" square post with 1/8" walls
- Surface mount (42")

SPECIFY MODEL

LIST

Model	Description	
CBC482A4U	42" surface mount, 6" square post, with high and low 4-1/2" SPDT switch plates	667.00
CBC484A4U	42" surface mount, 6" square post, with high and low 4-1/2" DPDT switch plates	717.00

Bollard Post

Distributor Discount Code **CK**



- For use with Push Plates, Touch Panel Columns & Exit Switches
- Black HDPE mortised removable cap with secure transmitter mount
- Standard single gang prep located at 36" from finished floor
- 6" square with 1/8" walls
- Surface mount (42") or In-Ground mount (54")

SPECIFY MODEL

LIST

Model	Description	
BPS6	42" surface mount, 6" square post	404.00
BPG6	54" in-ground, 6" square post	404.00

SPECIFY PREP

Add to List

S	1-gang prep	N/C
D	2-gang prep	N/C
P	Touch Panel prep	N/C
A	Narrow Mullion Prep	N/C

SPECIFY FINISH

Add to List

V 628 Aluminum (standard)	X 710 Dark Anodized Aluminum	N/C
----------------------------------	-------------------------------------	------------

400 Series Wireless Transmitter and Receiver

Distributor Discount Code **CK LIST**

For Remote Control Versatility for Touch Panel Column and Push Plate Switches



433MHz Micro Transmitter

- Requires a non-metallic surface box or standard bollard cap (non-metallic). Works with 400RC433
- Pre-Wired for quick installation
- Antenna magnifies signal

Voltage Input: 9V Battery (included)

Trigger Input: Momentary, N.O.Dry Contact

Temperature: -20F — 100F

Dimensions: 1-9/64" x 15/16" x 7/32" (29 x 49 x 6mm)

Model Description

400W1-433	433MHz Micro Transmitter	75.00
------------------	--------------------------	--------------



433MHz 1 Channel Nano Receiver

- Designed to control automatic closing and anti-burglar systems. Works with 400W1-433.

Carrier Frequency: 433.92 MHz

Power Supply: 12/24 VAC/DC

Relay Numbers: 1

Contacts: C-NO

Temperature: -4F — 158F

Dimensions: 1-1/4" x 2" x 3/4" Deep (32 x 51 x 19mm)

Model Description

400RC433	433MHz 1 Channel Receiver	88.00
-----------------	---------------------------	--------------

SDG

SECURITY DOOR CONTROLS
801 Avenida Acaso • Camarillo, CA 93012
Email: Service@sdgsecurity.com • www.sdgsecurity.com

Price List Effective February 1, 2017

For Handicap Access, Automatic Door Activation & Request-to-Exit Applications

- Door Opener Activation
- Automatic Door Activation
- Access Control Request-to-Exit (RTE)
- Door Sequencer Activation



= can be used with wireless transmitter and receiver

SPECIFICATIONS

Mounting Plate	Heavy Duty 1/8" (3.2mm) mounting plate
Faceplate	Heavy 18 Gauge (1.02mm), 630/US32D Satin Stainless Steel Standard
Legends	Bold debossing or engraving with black, blue or white infill
Contacts	SPDT or DPDT, 15 Amps @ 125/250VAC; UL 1054, CSA Listed
Depth	[Narrow & (1) Gang] SPDT-7/8" deep, DPDT-1-3/8" deep, [4 1/2", & 6" square/ round] SPDT-3/4" deep, DPDT-1-5/32"



1-11/16" Narrow Mullion Push Plate Switch – Recessed, Surface Box or Bollard Mount

SPDT Model	Description	DPDT Model	Description
48201U	Push to Open, black infill	65.00	48401U Push to Open, black infill 90.00
482A1U	Push to Open, blue infill	65.00	484A1U Push to Open, blue infill 90.00
400-1B	Narrow Mullion Surface Box, 1-3/4" x 4-9/16" x 1-3/4" O.D.		19.00



2 3/4" x 4 1/2" Single (1) Gang Push Plate Switch

- Pressing any part of the push plate (2 3/4" x 4 1/2") causes switch actuation
- Recessed, Surface Box or Bollard Mount
- Depth: SPDT - 3/4" deep; DPDT - 1 1/2" deep

SPDT Model	Description	DPDT Model	Description
48202U	Push to Open, black infill	77.00	48402U Push to Open, black infill 102.00
482A2U	Push to Open, blue infill	77.00	484A2U Push to Open, blue infill 102.00
480-2SB	Surface mount box, 2 3/4" x 4 1/2" x 1 5/8" O.D.		29.00



4 1/2" x 4 1/2" Square Push Plate Switches

- Pressing any part of the push plates 4 1/2" x 4 1/2" active area causes switch actuation
- 1 Gang or 2 gang recessed or Surface Box Mount
- Depth: SPDT 5/8" deep; DPDT 1 1/2" deep

SPDT Model	Description	DPDT Model	Description
48204U	Push to Open, black infill	85.00	48404U Push to Open, black infill 110.00
482A4U	Push to Open, blue infill	85.00	484A4U Push to Open, blue infill 110.00
480-4FB	Square Flush Recessed box, 1-gang, 6 3/4" x 6 3/4" x 1 7/8" O.D.		63.00
480-4SBB	Surface mount box, 4-1/2" x 4-1/2" x 1 3/4" O.D. with Battery compartment for wireless		33.00
480-4SB	Surface mount box, 4-1/2" x 4-1/2" x 1 7/8" O.D.		63.00
480-4SE	3-sided stainless shroud for exterior applications, 4-11/16" x 4-7/8" x 12"		38.00



6" x 6" Square Push Plate Switch

- Pressing any part of the push plates 6" x 6" active area causes switch actuation
- 1 Gang or 2 gang recessed or Surface Box Mount
- Depth: SPDT 5/8" deep; DPDT 1 1/2" deep

SPDT Model	Description	DPDT Model	Description
48206U	Push to Open, black infill	90.00	48406U Push to Open, black infill 114.00
482A6U	Push to Open, blue infill	90.00	484A6U Push to Open, blue infill 114.00
480-6SBB	Surface mount box, 2-gang Battery Compartment, 4 1/2" x 4 1/2" x 1 3/4" O.D.		33.00

Price List Effective February 1, 2017

SDC SECURITY DOOR CONTROLS
801 Avenida Acaso • Camarillo, CA 93012
Email: Service@sdsecurity.com • www.sdsecurity.com

