



www.sdcsecurity.com service@sdsecurity.com
 [t] 800.413.8783 805.494.0622 [f] 805.494.8861
 801 Avenida Acaso, Camarillo CA 93012 • PO Box 3670, Camarillo CA 93011-3670

Civic™ E72K-A Electronic Digital Lock

E72K-A Civic Series 160 User Electronic Digital Door Lock

Economically priced, the E72K-A Civic series electronic digital lockset incorporates the features required to manage most stand alone access control applications for up to 160 users.

The heavy duty weather resistant housing and keypad make the E72K-A ideal for indoor and outdoor applications.

Easily installed, the E72K-A retrofits mechanical cylindrical locks in only ten minutes. Additional benefits include the elimination of costly power supplies and labor intensive wiring and the elimination of key management.



Vandal Resistant Clutch

When locked, the outside lever is not rigid and will turn without retracting the latch, eliminating potential damage to internal parts from forcing lever handles.

Attributes

- ANSI Grade 2, cylindrical lockset
- Extra heavy duty indoor/outdoor all weather housing
- -32°F to +155°F (-35°C to 68°C)
- 4 x 4 metal alphanumeric keypad
- Clutch for lever vandal resistance
- Key override, Schlage C keyway std.
- Audible and LED indicator
- Real time clock
- 4AA batteries
- 2 stage low battery alert
- UL Listed for 3 Hr fire rated doors
- ADA compliant
- No audit trail

Programmable Features

- Keypad programmable
- 160 users
- Temp users schedules (64 users max)
- 9 management groups
- 90 user groups
- 16 button alphanumeric keypad
- 3 or 6 digit user code, ID + PIN or PIN only
- Auto Daylight Savings
- Manual passage mode
- Dual code entry capability by two users for high security applications



SECURITY DOOR CONTROLS


sdsecurity.com

service@sdsecurity.com



Price & Installation

Cylindrical Digital Locks



E72KA 160 user lockset



Levers



Galaxy (G)

Eclipse (E)

Lever Handles with Standard Key Cylinders

G1 Galaxy lever, 6 pin cylinder with Schlage "C" Keyway


E1 Eclipse lever, 6 pin cylinder with Schlage "C" Keyway

Finish



B Black Powder Coat case with Dull Chrome lever (*standard*)

Options



BS1 2.375" (60mm) backset

SK-1 Spacer kit for 1.375" door thickness

WGB E72 weldable gate box

Mechanical Specifications

Heavy Duty Cast Housing

Door Thickness	1-5/8" (41.2mm) - 1-7/8" (47.6mm) standard SK1 Spacer for 1-3/8" (35mm) door
Front	1-1/8" (28.6mm) x 2-1/4" (56.9mm)
Latchbolt	9/16" (14.3mm) throw, reversible
Backset	2-3/4" (70mm) standard
Strike	2-3/4" (70mm) standard ANSI
Keying	6 Pin with Schlage (C) keyway, 2 keys
Clutch	Lever clutch mechanism
Door Preparation	ANSI 115.18 door prep with additional 1.0" (19mm) through hole.
Nonhanded	

Compliances

ANSI A156.25, Electrified Lockset
ANSI A156.2, Grade 2
ANSI A117.1 Accessibility Code

ADA Compliant

California State Reference Code

Formerly Title 19, California State Fire Marshal, Levers Galaxy and Eclipse return to within .5" (13mm) of the door face.

UL Listings

UL Listed, USA & Canada for 3 hr "A" label fire rated doors.