

S6000 Spectra™ Series - S6000-E/EM

Electric Latch Retraction and Dogging



ELECTRIC LATCH RETRACTION

Electric Latch Retraction enables electric access control and dogging of mechanical exit devices. When energized the motor retracts the exit device latch and pulls the pushpad on most devices into the dogged (depressed) position enabling momentary or sustained push and pull operation of the door.



FEATURES

- Choice of Internal or External Module Electric Latch Retraction and Dogging
- Use for Rim, Surface Vertical or Mortise Exit Devices

MODELS

- E** Dual Electric Latch Retraction/Dogging
- EM** External Module Dual Electric Latch Retraction/Dogging

SPECIFICATIONS

Operation	Momentary or Maintained Latch Bolt and Push Pad Retraction, with Simultaneous Dogging. Automatic Re-Triggering of Latch Retraction
Finish	Dull Stainless Steel
Voltage	24VDC @ 700 mA Activation, 200 mA Continuous



HOW TO ORDER:

1| SPECIFY MODEL

- S61** Rim Mount
- S62** SVR Surface Vertical Rod
- S63** Mortise (03 Lever trim included)
Specify: **EE/GE** Eclipse or Galaxy Escutcheon

2| SPECIFY FUNCTION

- 02** Dummy Lever or Pull
- 03** Nightlatch, Lever or Pull, Key Latch Retraction

3| SPECIFY PANIC OR FIRE RATED

- P** Panic Exit Device
- F** Fire Exit Device

4| SPECIFY HAND

- RR** Right Hand Reverse Bevel, RHRB
- LR** Left Hand Reverse Bevel, LHRB

5| SPECIFY FINISH

- U** 630 Dull Stainless Steel

6| SPECIFY LENGTH

- 36** For 36" Door
- 42** For 42" Door
- 48** For 48" Door

7| SPECIFY ELECTRIC LATCH RETRACTION

- E** Dual Electric Latch Retraction Dogging
- EM** External Module Dual Electric Latch Retraction/Dogging (8 Wires Req'd)

8| SPECIFY TRIM

FOR MORTISE S63 ONLY (LESS CYLINDER)

- EE** Eclipse Escutcheon
- GE** Galaxy Escutcheon

8| SPECIFY TRIM (OPTIONAL) RIM S61 AND SURFACE S62 ONLY

Mechanical Trim (less cylinder)

- EK02U** Dummy Eclipse Escutcheon
- GK02U** Dummy Galaxy Escutcheon
- SP02U** Dummy Saturn Escutcheon
- EK03U** Eclipse Escutcheon
- GK03U** Galaxy Escutcheon
- SP03U** Saturn Escutcheon



SPECIFY TRIM OPTIONS:

Rim Cylinder Required for 03 function, Mortise Cylinder Required for S6300

- CYL-6KDQ** 6 pin, 1.125" Mortise Cylinder, Keyed Different, Dull Chrome
- CYL-6KAQ** 6 pin, 1.125" Mortise Cylinder, Keyed Alike, Dull Chrome
- RIM-CYL-KA** 6-pin Rim Cylinder, Keyed Alike, Specifically For EK03, GK03

ACCESSORIES

- PTH-4Q** Four Wire, Dull Chrome Power Transfer Hinge
- PTH-10Q** Ten Wire, Dull Chrome Power Transfer Hinge



- PTM-2AL** Aluminum Powder Coat 2 Wire, US28 equivalent
- PTM-2BZ** Dark Brown Powder Coat 2 Wire, US10B equivalent
- PTM-10AL** Ten Wire Aluminum Powder Coat, US28 equivalent
- PTM-10BZ** Ten Wire Aluminum Powder Coat, US10B equivalent, Dark Brown Powder Coat



- 602RF** 1 Amp, 12/24 VDC Class 2 Output Power Supply, 12" W x 12" H x 3.75" D Box
- 631RF** 1.5 Amp, 12/24 VDC Class 2 Output Power Supply, 12" W x 12" H x 3.75" D Box
- EMC** 2 Station Door Sequencer
Each EMC provides interface and sequencing for two single or one double automatic door. Not required for manual doors.

