ELECTRA PRO™ SDC' Z7200 Series Heavy Duty Cylindrical Locksets

Distributor Discount Code **LEK**

Function: 7200 Series Locksets are locked on the outside and unlocked from the exterior by an access control or mechanical key. The inside lever is always operable for uninhibited egress.
Latch Status Output: Standard with all SDC brand Z7200 locksets. SPDT, 3 Amps @ 30VDC

FEATURES

- Choice of failsecure or failsafe mode
- Dual 12/24 VDC
- **Latch Status Output:** Z7200 standard
- 'C' type keyway, BEST IC core optional
- Independent lever power return springs
- Power Regulator Module included

SPECIFICATIONS

UL LISTED — Electrically Controlled Single Point Locks & Latches, 3 Hr A Label Fire Doors — CSFM 3773-0324:104

Dual Voltage	600/300 mA @ 12/24VDC	**Backset**	2.75
Certification	Exceeds ANSI A156-2-4000 Grade 1	**Strike**	4.875 strike ANSI A115.2
		Door Thickness	1-5/8" to 2-1/8"
Latchbolt	0.5625"		

Electra Pro™ Z7250G

Electra Pro™ Z7250E

SPECIFY MODEL — LIST

Electra Pro™ Locks

Z7250	SDC Failsafe, with Latch Status Output	**Z7252**	SDC Failsecure, with Latch Status Output	**449.00**

SPECIFY LEVER TRIM

SDC Lever Trim

G	Galaxy	**E**	Eclipse	**N/C**
G5	**Galaxy, I-Core prep**	**E5**	**Eclipse, I-Core prep**	**27.00**

G5 and E5 I-Core prep without I-Core

G Galaxy

E Eclipse

G5 Galaxy, I-Core prep

E5 Eclipse, I-Core prep

I-CORE

SPECIFY FINISH — Add to List

Q	626 Dull Chrome (standard)	**N/C**			
C	605 Bright Brass	**54.00**	**H**	613 Oil Rubbed Bronze	**54.00**
D	606 Dull Brass	**54.00**	**P**	625 Bright Chrome	**54.00**

OPTIONS — Add to List

R	Request-to-exit output, operates on activation of inside lever, SPDT 0.1A @ 30VDC	**124.00**

NOTE: REX Output Replaces Latch Status Output

OPTIONAL CYLINDER and I-CORES — Add to List

SDC Conventional Cylinders (Schlage 'C' Keyway Standard)

6PKA	6 PIN Keyed alike	**N/C**	**6PKD**	6 PIN Keyed different (standard)	**N/C**

[IC] Interchangeable Core (Best 'A' Keyway Standard) - <u>requires E5 or G5 lever trim</u>

IC7P-KA	7 pin I-Core, small format, keyed alike	**54.00**	**IC7P-KD**	7 pin I-Core, small format, keyed different	**54.00**

OPTIONAL LATCH AND BACKSET ASSEMBLIES

B1	2-3/4" Backset latchbolt (Standard)	**N/C**	**B2**	2-3/8" Backset latchbolt (Optional)	**25.00**

OPTIONAL STRIKE PLATES

ST1	ANSI 1-1/4" x 4-7/8" (Standard)	**N/C**	**ST2**	T-Strike with dust box, 1-1/8" x 2-3/4" MUST BE SPECIFIED	**N/C**

SDC SECURITY DOOR CONTROLS
801 Avenida Acaso • Camarillo, CA 93012
Email: Service@sdcsecurity.com • www.sdcsecurity.com