

SELECTRIC® Pro Locksets incorporate an SDC manufactured Grade 1 Heavy Duty mortise lockset and vandal resistant clutch mechanism. Proprietary to SDC, SELECTRIC® Pro locksets. All operational attributes are field selectable. In addition, SELECTRIC® Pro locksets retrofit many other mechanical lock brands making them fully compatible with new and retrofit applications.

FIELD SELECTABLE ATTRIBUTES


- Selectable mode, failsafe or failsecure
- Selectable function, locked outside only or both sides
- Selectable voltage, 12 or 24VDC
- Selectable handing



Electrically Controlled
Single Point Locks or
Latches
3 Hr A Label Fire
Rated Doors



3773-0324:104



Price List Effective February 1, 2017

Electrified Locksets



SPECIFY FUNCTION AND MODE [] [] [] [] [] **LIST**

SDC Supplied Electrified Lock (Mortise cylinder not included). SDC Brand 7800 lockset. Clutch for lever trim vandal resistance. * Less trim - compatible with Schlage trim

| | | * Less Trim | With SDC Trim |
|--------------|---|---------------|---------------|
| Z7830 | Locked both sides, failsafe. Field reversible to failsecure mode. | 306.00 | 735.00 |
| Z7850 | Locked outside only, failsafe. Field reversible to failsecure mode. | 306.00 | 735.00 |
| Z7832 | Locked both sides, failsecure. Field reversible to failsafe mode. | 306.00 | 735.00 |
| Z7852 | Locked outside only, failsecure. Field reversible to failsafe mode. | 306.00 | 735.00 |
| Z7835 | Locked outside and/or inside. Outside failsecure, inside failsafe | 466.00 | 849.00 |

VOLTAGE - Z7835 ONLY [] [] [] [] []

Specify voltage for Z7835 function only. Leave blank for all other functions which are 12/24VDC, field selectable

| 12 12VDC | 24 24VDC | N/C |
|----------|----------|-----|
| [] | [] | [] |

SPECIFY HAND [] [] [] [] []

| | | | |
|---------------------|-------------------------------|---------------------------------------|------------|
| L Left hand | LR Left hand reversed | All hands are field reversible | N/C |
| R Right hand | RR Right hand reversed | without disassembly (exception Z7835) | N/C |

SPECIFY FINISH [] [] [] [] [] **Add to List**

| | | | |
|-------------------------------------|--------------|-----------------------------------|--------------|
| Q 626 Dull Chrome (standard) | N/C | | |
| C 605 Bright Brass | 52.00 | G 612 Dull Bronze | 52.00 |
| D 606 Dull Brass | 52.00 | H 613 Oil Rubbed Bronze | 52.00 |
| F 611 Bright Bronze | 52.00 | U 630 Dull Stainless Steel | 52.00 |
| | | P 625 Bright Chrome | 52.00 |

SPECIFY LEVER TRIM [] [] [] [] [] **Add to List**

| | | | |
|---|------------|--|---------------|
| G Galaxy with rose | N/C | GE Galaxy with escutcheon | 104.00 |
| E Eclipse with rose | N/C | EE Eclipse with escutcheon | 104.00 |
| N Nova with rose | N/C | NE Nova with escutcheon | 104.00 |
| 07 Schlage equal with SDC B rose | N/C | 07E Schlage equal with SDC escutcheon | 104.00 |

OPTIONS AND ACCESSORIES **Add to List**

Optional Outputs




| | |
|--|---------------|
| R Request-to-exit. Indicates inside lever operation for access control request-to-exit input, alarm shunt, remote annunciation or CCTV activation, SPDT 5 Amp @ 30VDC | 83.00 |
| D Door position status output. Indicates door open and door closed. SPDT 5 Amp @ 30VDC. | 83.00 |
| S Latched & locked status output. Indicates door latched and locked and door unlocked. SPDT 5 Amp @ 30VDC | 104.00 |

Optional Cable and Connectors

| | |
|---|--------------|
| CC1-5 5ft. Cable and connectors for locks without optional outputs | 47.00 |
| CC3-5 5ft. Cable and connectors for locks with optional outputs | 63.00 |
| Optional Key Cylinders 1 required for 7850/7852 2 required for 7830/7832 | 32.00 |
| CYL-6KDQ 6 pin, 1.125" keyed different, 626 Dull Chrome | 32.00 |
| CYL-6KAQ 6 pin, 1.125" keyed alike, 626 Dull Chrome | 32.00 |

Power Transfer Hinge
UL listed, 4.5", five knuckle hinge. Special finish available

| | |
|--|---------------|
| PTH-4Q Four wire, dull chrome | 156.00 |
| PTH-10Q Ten wire, dull chrome | 202.00 |
| PTH-2+4Q 6-wire Electric Hinge 1-pair 16 Amp inrush, 4 Amp continuous;2-pair 1 Amp @ 12/24V | 182.00 |



PTH
UL 10B Listed for 3Hr
Fire Rated Doors
See page XX

SECURITY DOOR CONTROLS

801 Avenida Acaso • Camarillo, CA 93012

Email: Service@sdsecurity.com • www.sdsecurity.com

