

Conventional Mortise Bolt Locks

Distributor Discount Code **AK LIST**

110/160 Dual Voltage Coil: 900/450 mA @ 12/24 VDC
210/260 Dual Voltage Coil: 900/450 mA @ 12/24 VDC
 Mortise strike standard.
Not for use in wood frames.



110
210

5" depth required

110IV	2-3/4" x 1-1/4" Face plate, less auto relock switch, failsafe V 628 Aluminum (standard)	193.00
210HV	2-3/4" x 1-1/4" Face plate, less auto relock switch, failsecure V 628 Aluminum (standard)	193.00
160IV	4-7/8" x 1-1/4" Face plate with auto relock switch, failsafe V 628 Aluminum (standard)	257.00
260HV	4-7/8" x 1-1/4" Face plate with auto relock switch, failsecure V 628 Aluminum (standard)	257.00



160
260

SPECIFY ADD-ON

Add to List

MC-4	External recessed magnetic (3/4", SPDT, 30VDC, 50mA)	52.00
-------------	--	--------------

Electric Bolt Locks


Surface Mount Bolt Locks

Distributor Discount Code **AK LIST**



180/280

Dimensions: 6" L x 2" W x 2" H
180 Dual Voltage Coil: 900/450 mA @ 12/24 VDC
280 Dual Voltage Coil: 900/450 mA @ 12/24 VDC



Surface Mount
Outswing Door


MODEL

180AIV	Surface mount, failsafe, with auto relock, Aluminum standard	279.00
280AHV	Surface mount, failsecure with auto relock, Aluminum standard	279.00

SPECIFY ADD-ON

Add to List

D	External recessed magnetic (3/4", SPDT, 30VDC, 50mA) MC-4	52.00
----------	---	--------------



Top Jamb
Inswing or Sliding
Door