



1190 / 2090 Series

Heavy Duty Right Angle
Electric Bolt Locks

Designed and patented by SDC, Spacesaver® right angle bolt locks represent a fundamental innovation in electric locking technology for access control applications. Spacesaver® bolts project at right angles to the lock mechanism, allowing installation of Spacesaver® locks, by means of a simple mortise cutout, in virtually any standard frame, or in most door lock styles. With the entire lock concealed, aesthetic acceptability is complete, security is greater and installation in old or new construction is fast, easy and economical.

1190A and 2090A models utilize a 3/4" diameter solid stainless steel bolt, an extra heavy duty housing design and solenoid. Designed to provide years of trouble free operation, 1190A and 2090A bolt locks are the most powerful commercial grade units available on the market. There are only three moving parts within the hefty solid metal body of the 1190A and only five moving parts in the 2090A. The power and strength of the solenoids far surpass any competitive models.

- Concealed mortise right angle design
- Stainless steel bolt
- Specification grade solenoid
- Automatic relock
- Field adjustable and bidirectional automatic relock ball switch
- Mounting tabs included
- Voltage and current spike protection
- Power regulator included

ORDERING GUIDE

	FUNCTION		OPTIONS	
	I		D	
	IWD		B	
	H			
1190A	I	U	D B	
1190A	FINISH			
2090A				
MODEL				

NOT REQUIRED

EXAMPLES

1190AIU	Heavy Duty Right Angle Bolt Lock, Failsafe, 630	483.00
1190AIUDB	Heavy Duty Right Angle Bolt Lock, Failsafe, 630, DPS, BPS	613.00
1190AIWDU	Heavy Duty Right Angle Bolt Lock, Failsafe, Wood Applications, 630	575.00
2090AHU	Heavy Duty Right Angle Bolt Lock, Failsecure, 630	602.00
2090AHUDB	Heavy Duty Right Angle Bolt Lock, Failsecure, 630, DPS, BPS	732.00

1190/2090 CONFIGURATION 1 of 1



1190A




2090A

MODEL		LIST \$
	●○○○	
1190A	Heavy Duty Right Angle Bolt Lock, Failsafe	483.00
2090A	Heavy Duty Right Angle Bolt Lock, Failsecure	602.00

FUNCTION		ADD TO LIST
	○●○○	
I*	Failsafe	N/C
IWD*	Wood Applications, Failsafe	92.00
H**	Failsecure	N/C

*For 1190A failsafe models only.

**For 2090A failsecure models only.

FINISH		ADD TO LIST
	○○●○	
U	630 Dull Stainless 	N/C

OPTIONS		ADD TO LIST
	○○○●	
D	Door Position Status (DPS)	65.00
B	Bolt Position Status (BPS)	65.00