



# 1561S Series

Surface Electromagnetic Shear Locks

SDC's HiShear® electromagnetic shear locks are designed, engineered and built in America for openings that require an architecturally superior appearance. Long recognized as a cut above alternatives on the market, SDC shear locks provide high security with a failsafe locking mechanism to meet a variety of door opening applications.

1561S models are surface mounted to the push side of an out-swing door.

- Surface mount design
- Floating armature assembly
- Special alloy steel shear tabs
- Auto-sensing dual voltage
- Door alignment relock sensor
- Adjustable lateral and vertical alignment
- Noise dampeners

## ORDERING GUIDE

|       |        |         |
|-------|--------|---------|
|       | FINISH |         |
|       | V      |         |
|       | Y      |         |
|       | C      |         |
|       | X      |         |
|       | Q      |         |
|       | P      |         |
| 1561S | V      | DPS BA  |
| MODEL |        | DPS     |
|       |        | BA      |
|       |        | L3      |
|       |        | OPTIONS |

NOT REQUIRED 

## EXAMPLES

|                      |   |                 |
|----------------------|---|-----------------|
| <b>1561SV</b>        | Surface Shear Lock, Integrated Electronics, 2000lbs, 628                | <b>1,212.00</b> |
| <b>1561SVDPS</b>     | Surface Shear Lock, Integrated Electronics, 2000lbs, 628, DPS           | <b>1,271.00</b> |
| <b>1561SVDPSBA</b>   | Surface Shear Lock, Integrated Electronics, 2000lbs, 628, DPS, BAS      | <b>1,400.00</b> |
| <b>1561SVDPSBAL3</b> | Surface Shear Lock, Integrated Electronics, 2000lbs, 628, DPS, BAS, LED | <b>1,420.00</b> |
| <b>1561SY</b>        | Surface Shear Lock, Integrated Electronics, 2000lbs, 335                | <b>1,283.00</b> |

### COMPONENT CONSIDERATIONS

With a robust toolbox of over 35,000 SDC access & control components at your fingertips, you can add additional components to complement the products you're ordering and assemble a turnkey solution for almost any controlled door opening system imagined.



Keypads & Readers

[CLICK TO VIEW](#)



Egress Devices

[CLICK TO VIEW](#)



Exit Switches & Sensors

[CLICK TO VIEW](#)



Emergency Door Releases

[CLICK TO VIEW](#)



Power Controllers

[CLICK TO VIEW](#)



Door Controls & Backup Batteries

[CLICK TO VIEW](#)



Remote Control Consoles

[CLICK TO VIEW](#)



Door Prop Alarms & Annunciators

[CLICK TO VIEW](#)

## 1561S CONFIGURATION 1 of 1

| MODEL        |   | LIST \$         |
|--------------|---|-----------------|
| <b>1561S</b> | Surface Shear Lock, Integrated Electronics, 2000lbs | <b>1,212.00</b> |

| FINISH   |   | ADD TO LIST   |
|----------|---|---------------|
| <b>V</b> | 628 Dull Aluminum <small>Standard</small> | <b>N/C</b>    |
| <b>Y</b> | 335 Dull Black                            | <b>71.00</b>  |
| <b>C</b> | 605 Bright Brass                          | <b>71.00</b>  |
| <b>X</b> | 710 Dark Bronze                           | <b>94.00</b>  |
| <b>Q</b> | 626 Dull Chrome                           | <b>222.00</b> |
| <b>P</b> | 625 Bright Chrome                         | <b>222.00</b> |

| OPTIONS    |                               | ADD TO LIST   |
|------------|-------------------------------|---------------|
| <b>DPS</b> | Door Position Status (DPS)    | <b>59.00</b>  |
| <b>BA</b>  | Bond Alert Status (BAS)       | <b>129.00</b> |
| <b>L3*</b> | Visual Status Indicator (LED) | <b>20.00</b>  |

\*Mounts separately through the frame and may be used to indicate lock is energized or wired to monitoring contacts.