



**ANSI/BHMA A156.24
Grade 1**



3774-0324:103



1581S

SDC PUSH UNTIL ALARM SOUNDS. DOOR CAN BE OPENED IN 15 SECONDS.

1581S	Single Mini Delayed Egress Lock 650 lbs. holding force. Current: 320/500 mA @ 24VDC/12VDC	979.00
--------------	---	---------------

Specify 2 for pairs of doors
Remote reset control required. See below.
Lock size 10" L x 2" H x 2-3/8" D

SPECIFY OPERATION

Specify ND, NC, NH, BC, BD, BH - see codes and description on page 18
If no Code is specified - ND is the SDC STANDARD OPERATIONS MODE for this product

SPECIFY FINISH **Add to List**

Anodized Finishes

V	628 Clear Anodized Aluminum (<i>standard</i>)	N/C
Y	335 Black Anodized	88.00

Powder Coat Finishes

(a coating electrostatically applied to form a hard finish, that is tougher than conventional paint)

X	Dark Bronze Powder Coat Painted (313/613 Equal)	88.00	C	Bright Brass Powder Coat Painted	88.00
D	Dull Brass Powder Coat Painted	88.00			

Plated Finishes. Special order, no cancellations or returns

P	625 Bright Chrome	211.00	Q	626 Dull Chrome	211.00
----------	-------------------	---------------	----------	-----------------	---------------

SPECIFY OPTIONS **Add to List**

D	Door position status	67.00
B	Magnetic bond sensor (Not an output. Low Holding Force. Put unit into alarm.)	112.00

TANDEM CABLE FOR PAIR OF DOORS **LIST**

Required when using two locks on a pair of doors, cables enable auxiliary lock operation.

1581S-TC-3	Cable kit for connecting two locks through the frame header, 3ft	34.00
1581S-TC-10	Cable kit for wiring for two locks, 10ft	45.00

SPECIFY RESET AND CONTROL DEVICE **LIST**

Select Reset Station for NC and ND functions

918	EntryCheck™ digital keypad, 500 user codes Keyless Reset / manual power up / bypass	177.00
728	Key switch, 2 keys, 1 gang Reset / manual power up / sustained bypass	67.00
728L3	Key switch, 2 keys, 1 gang, LED status indicator Reset / manual power up / sustained bypass	93.00
702R	Separate wall mount reset key switch assembly MO SPDT dry contact, 6 Amp @ 30VDC max. Accepts standard 1-1/8" to 1-1/4" (Mortise key cylinder not included)	122.00
101-1AK	Key switch assembly, 2 gang, LED status indicator, less cylinder Reset / manual power up / sustained bypass	355.00
101-4AM	Four station remote annunciator	355.00



918



728



702R



101-1AK



101-4AM