

410 SERIES - 1-3/4" X 1" EXIT SWITCH **OPTIONS - SEE PAGE 80** **LIST**

1 3/4" x 1" Button - Green and Red Illuminated Lens included - Dull Stainless Steel finish

NOTE: AA Models Are Not Illuminated



412N
413N
414N

Narrow	Contact	Sign	
412NU	Momentary SPDT	PUSH TO EXIT	76.00
413NU	Integrated electronic timer, adj. 1-60 sec. 12/24VDC, 2A DPDT Contact	PUSH TO EXIT	145.00
413PNU	Integrated pneumatic timer, adj. 1-180 sec. 12/24VDC, SPDT 3 Amp Contact	PUSH TO EXIT	342.00
414NU	Momentary DPDT	PUSH TO EXIT	91.00
415NU	AA (On/Off) DPDT	NONE	113.00

420 SERIES - 2" EXIT SWITCH **OPTIONS - SEE PAGE 80** **LIST**

2" Button, Green and Red Illuminated Lens included - Dull Stainless Steel Finish

NOTE: AA Models Are Not Illuminated



422 422A
423 423A
424

1 Gang	Contact	Sign	
422U	Momentary SPDT	PUSH TO EXIT	76.00
422AU	Momentary SPDT 2" Button - Blue illuminated lens only	♿ Symbol	76.00
423U	Integrated electronic timer, adj. 1-60 sec 12/24VDC, 2A DPDT Contact	PUSH TO EXIT	145.00
423PU	Integrated pneumatic timer, adj. 1-180 sec. 12/24VDC, SPDT 3 Amp Contact	PUSH TO EXIT	342.00
423AU	Integrated 1-60 sec Timer 12/24VDC, 2A DPDT Contact 2" Button - Blue illuminated lens only	♿ Symbol	145.00
424U	Momentary DPDT	PUSH TO EXIT	113.00
425U	AA (On/Off) DPDT	NONE	113.00

CODE COMPLIANT MANUAL RELEASE DEVICES **LIST**

Code Compliant Manual Releasing Devices and Sensors

423M and 413MN exit switches USED TOGETHER WITH the MD31D PIR sensor comply with manual releasing device and sensor device requirements for Access-Controlled Egress Doors per:

IBC International Code 1008.1.3.4 NFPA 101 7.2.1.62 BOCA National Building Code 1017.4.5
IFC International Code 1008.1.3.4 NFPA 1 15.5.3.2 SBCCI Standard Building Code 1012.7

Code Compliant Manual Release Device

Code Compliant Features: Fixed 30 second timer, re-triggerable; Failsafe - lock releases when power to switch is interrupted; Sign - PUSH TO EXIT; CSFM Listed::

1 3/4"x1" Button, Green Illuminated Lens - Dull Stainless Steel Finish, Specify R for optional red lens



413MN 423M

Narrow	Contact	Sign	
413MNU	Integrated Fixed 30 sec. Timer 12/24VDC, 2 Amp Contact	PUSH TO EXIT	150.00

2" Button, Green Illuminated Lens - Dull Stainless Steel Finish, Specify R for optional red lens

1 Gang	Contact	Sign	
423MU	Integrated Fixed 30 sec. Timer 12/24VDC, 2 Amp Contact	PUSH TO EXIT	150.00

Code Compliant Egress Sensor

Code Compliant Features: PIR egress sensor with failsafe mode - lock releases when PIR power to PIR sensor is interrupted. UL listed 294 Access Control System Units



MD-31DOW



MD-31DB



Model	Color		
MD-31DOW	White	PIR Egress Sensor	V 243.00
MD-31DB	Black	PIR Egress Sensor	V 243.00

Input: 12 or 24 VAC/DC @ 26mA max.

Contact: 2 SPDT Dry, 2 Amp @ 30VDC (38.1 H x 148.8 W x 38.1 D mm)

Operating Temp: -20° F to 120° F (-29° C to 49° C)

Dimensions: 1.5" H x 6.25" W x 1.5" D



BB1D

RETROFIT BACK BOX **LIST**

BB1D	Single Gang 2.25" w x 3.75" h x 2.75" D	14.00
-------------	---	--------------



430 430N



432KLD

430 SERIES - 1-1/2" MUSHROOM EXIT SWITCH - FOR OPTIONS SEE BELOW LIST

1.5" Mushroom, Green Button Standard, Dull Stainless Steel Finish, Specify R For Optional Red Button

1 Gang	Narrow	2 Gang	Contact	Sign	
431CU	431CNU		AA (On/Off) NC SPST	none	118.00
431OU	431ONU		AA (On/Off) NO SPST	none	118.00
432CU	432CNU		Momentary NC SPST	EXIT	118.00
432OU	432ONU		Momentary NO SPST	EXIT	118.00
432KUR	432KNUR		Latching/ key reset DPST, Red	none	230.00
432KLDUR			Lockdown, DPST, Key Reset	LOCKDOWN	247.00
432KLDURL2			Lockdown, DPST, Key Reset, 1 Red and 1 Green LED	LOCKDOWN	280.00
		433U	Momentary with Timer Module 1-60 sec. EXIT 12/24V AC/DC SPDT 2A Contact		220.00
434U	434NU		Momentary DPST	EXIT	145.00
435U	435NU		AA (On/Off) DPST	none	145.00

440 SERIES - 2-5/8" MUSHROOM EXIT & PANIC SWITCHES - FOR OPTIONS SEE BELOW LIST

2-5/8" Mushroom, Red Button Standard, Dull Stainless Steel Finish, Specify G For Optional Green Button




441 - 444 446

1 Gang	2 Gang	Contact	Sign	
	441U	AA (On/Off) DPST	None	203.00
	442U	Momentary DPST	EXIT	203.00
	443U	Momentary with Timer Module 1-60 sec. EXIT 12/24V AC/DC SPDT 2A Contact		294.00
	444U	Momentary 2-DPST	EXIT	225.00
	446U	Momentary DPST	EXIT	134.00

463 SERIES - VANDAL RESISTANT STAINLESS STEEL EXIT SWITCH LIST

Capacitive Stainless Steel Button - No moving parts - Integrated Time Delay - Red and Green Status Indicators
2mm Stainless Steel - Security Screws - Plated Finish Not Available



463 463N

1 Gang	Narrow	Contact	Sign	
463U	463NU	Integrated 1-40 Sec Timer 12/24VDC, SPDT 1A Contact	PUSH TO EXIT	140.00

470 SERIES - SANITARY, NO TOUCH, WAVE-TO-EXIT SWITCH LIST

- IR Sensor, 4" read range, Red, Green illuminated LED status. Control electric locks, strikes and automatic door operators.
 - Entry/exit for sanitary environments including: bathrooms, hospitals, schools, cleanrooms, food processing, labs, or offices.
- Output:** DPDT 3 Amp Dry Contact
Input: 25mA (standby); 55mA (active) @ 12/24VDC
Faceplate: 20ga stainless steel



474

	Contact	Sign	
474U	DPDT	No Touch Exit	81.00
474DU	DPDT	No Touch Exit	140.00

OPTIONS AND FINISHES FOR 410, 420, 430, AND 440 SERIES Add to List

Options for 410, 420, 430, 440 Series

L1G	1 Green LED	22.00	LT	Tricolor LED - Red, Green, Amber	33.00
L1R	1 Red LED	22.00	E	Add Exit sign To AA Function Switch Only	12.00
L2	1 Red and 1 Green LED	33.00	B	No Exit sign (None) with Momentary Switch	N/C

Special Finish

450 / 460 / 470 Special finish is not available
Designate special finish suffix from below in lieu of U (stainless steel) in part number.

C	605 Bright Brass	D	606 Dull Brass	44.00
P	625 Bright Chrome	H	613 Oil Rubbed Bronze	44.00



SECURITY DOOR CONTROLS
801 Avenida Acaso • Camarillo, CA 93012
Email: Service@sdcsecurity.com • www.sdcsecurity.com