

410 SERIES - 1-3/4" X 1" EXIT SWITCH OPTIONS - SEE PAGE 82 LIST

1 3/4" x 1" Button - Green and Red Illuminated Lens included - Dull Stainless Steel finish

NOTE: AA Models Are Not Illuminated

Narrow	Contact	Sign		
412NU	Momentary SPDT	PUSH TO EXIT		77.00
413NU	Integrated electronic timer, adj. 1-60 sec. 12/24VDC, 2A DPDT Contact	PUSH TO EXIT	UL 294	150.00
413PNU	Integrated pneumatic timer, adj. 1-180 sec. 12/24VDC, SPDT 3 Amp Contact	PUSH TO EXIT		355.00
414NU	Momentary DPDT	PUSH TO EXIT		94.00
415NU	AA (On/Off) DPDT	NONE		117.00



412N
413N
414N

420 SERIES - 2" EXIT SWITCH OPTIONS - SEE PAGE 83 LIST

2" Button, Green and Red Illuminated Lens included - Dull Stainless Steel Finish

NOTE: AA Models Are Not Illuminated

1 Gang	Contact	Sign		
422U	Momentary SPDT	PUSH TO EXIT		77.00
422AU	Momentary SPDT 2" Button - Blue illuminated lens only	♿ Symbol		79.00
423U	Integrated electronic timer, adj. 1-60 sec 12/24VDC, 2A DPDT Contact	PUSH TO EXIT	UL 294	150.00
423PU	Integrated pneumatic timer, adj. 1-45 sec. 12/24VDC, SPDT 3 Amp Contact	PUSH TO EXIT		355.00
423AU	Integrated 1-60 sec Timer 12/24VDC, 2A DPDT Contact 2" Button - Blue illuminated lens only	♿ Symbol		150.00
424U	Momentary DPDT	PUSH TO EXIT		117.00
425U	AA (On/Off) DPDT	NONE		117.00



422
423
424 422A
423A

CODE COMPLIANT MANUAL RELEASE DEVICES LIST

Code Compliant Manual Releasing Devices and Sensors

423M and 413MN exit switches USED TOGETHER WITH the MD31D PIR sensor comply with manual releasing device and sensor device requirements for Access-Controlled Egress Doors per:

IBC International Code 1008.1.3.4 NFPA 101 7.2.1.62 BOCA National Building Code 1017.4.5
IFC International Code 1008.1.3.4 NFPA 1 15.5.3.2 SBCCI Standard Building Code 1012.7

Code Compliant Manual Release Device

Code Compliant Features: Fixed 30 second timer, re-triggerable; Failsafe - lock releases when power to switch is interrupted; Sign - PUSH TO EXIT; CSFM Listed::

1 3/4"x1" Button, Green Illuminated Lens - Dull Stainless Steel Finish, Specify R for optional red lens

Narrow	Contact	Sign		
413MNU	Integrated Fixed 30 sec. Timer 12/24VDC, 2 Amp Contact	PUSH TO EXIT	UL 294	153.00

2" Button, Green Illuminated Lens - Dull Stainless Steel Finish, Specify R for optional red lens

1 Gang	Contact	Sign		
423MU	Integrated Fixed 30 sec. Timer 12/24VDC, 2 Amp Contact	PUSH TO EXIT	UL 294	153.00

Code Compliant Egress Sensor

Code Compliant Features: PIR egress sensor with failsafe mode - lock releases when power to PIR sensor is interrupted. UL listed 294 Access Control System Units

Model	Color			
MD-31DOW	White	PIR Egress Sensor		243.00
MD-31DB	Black	PIR Egress Sensor		243.00

Input: 12 or 24 VAC/DC @ 26mA max.

Contact: 2 SPDT Dry, 2 Amp @ 30VDC (38.1 H x 148.8 W x 38.1 D mm)

Operating Temp: -20° F to 120° F (-29° C to 49° C)

Dimensions: 1.5" H x 6.25" W x 1.5" D

RETROFIT BACK BOX

BB1D	Single Gang 2.25" w x 3.75" h x 2.75" D	15.00
------	---	-------



413MN 423M



MD-31DOW



MD-31DB



BB1D