

410 SERIES - 1-3/4" X 1" EXIT SWITCH OPTIONS - SEE PAGE 82 LIST

1 3/4" x 1" Button - Green and Red Illuminated Lens included - Dull Stainless Steel finish

NOTE: AA Models Are Not Illuminated



412N
413N
414N

Narrow	Contact	Sign		
412NU	Momentary SPDT	PUSH TO EXIT		77.00
413NU	Integrated electronic timer, adj. 1-60 sec. 12/24VDC, 2A DPDT Contact	PUSH TO EXIT	UL 294	150.00
413PNU	Integrated pneumatic timer, adj. 1-180 sec. 12/24VDC, SPDT 3 Amp Contact	PUSH TO EXIT		355.00
414NU	Momentary DPDT	PUSH TO EXIT		94.00
415NU	AA (On/Off) DPDT	NONE		117.00

420 SERIES - 2" EXIT SWITCH OPTIONS - SEE PAGE 83 LIST

2" Button, Green and Red Illuminated Lens included - Dull Stainless Steel Finish

NOTE: AA Models Are Not Illuminated



422
423
424

422A
423A

1 Gang	Contact	Sign		
422U	Momentary SPDT	PUSH TO EXIT		77.00
422AU	Momentary SPDT 2" Button - Blue illuminated lens only	♿ Symbol		79.00
423U	Integrated electronic timer, adj. 1-60 sec 12/24VDC, 2A DPDT Contact	PUSH TO EXIT	UL 294	150.00
423PU	Integrated pneumatic timer, adj. 1-45 sec. 12/24VDC, SPDT 3 Amp Contact	PUSH TO EXIT		355.00
423AU	Integrated 1-60 sec Timer 12/24VDC, 2A DPDT Contact 2" Button - Blue illuminated lens only	♿ Symbol		150.00
424U	Momentary DPDT	PUSH TO EXIT		117.00
425U	AA (On/Off) DPDT	NONE		117.00

CODE COMPLIANT MANUAL RELEASE DEVICES LIST

Code Compliant Manual Releasing Devices and Sensors

423M and 413MN exit switches USED TOGETHER WITH the MD31D PIR sensor comply with manual releasing device and sensor device requirements for Access-Controlled Egress Doors per:

IBC International Code 1008.1.3.4 NFPA 101 7.2.1.62 BOCA National Building Code 1017.4.5
IFC International Code 1008.1.3.4 NFPA 1 15.5.3.2 SBCCI Standard Building Code 1012.7

Code Compliant Manual Release Device

Code Compliant Features: Fixed 30 second timer, re-triggerable; Failsafe - lock releases when power to switch is interrupted; Sign - PUSH TO EXIT; CSFM Listed::



413MN

423M



1 3/4"x1" Button, Green Illuminated Lens - Dull Stainless Steel Finish, Specify R for optional red lens


Narrow	Contact	Sign		
413MNU	Integrated Fixed 30 sec. Timer 12/24VDC, 2 Amp Contact	PUSH TO EXIT	UL 294	153.00

2" Button, Green Illuminated Lens - Dull Stainless Steel Finish, Specify R for optional red lens

1 Gang	Contact	Sign		
423MU	Integrated Fixed 30 sec. Timer 12/24VDC, 2 Amp Contact	PUSH TO EXIT	UL 294	153.00

Code Compliant Egress Sensor

Code Compliant Features: PIR egress sensor with failsafe mode - lock releases when power to PIR sensor is interrupted. UL listed 294 Access Control System Units



MD-31DOW

MD-31DB



Model	Color			
MD-31DOW	White	PIR Egress Sensor		243.00
MD-31DB	Black	PIR Egress Sensor		243.00

Input: 12 or 24 VAC/DC @ 26mA max.

Contact: 2 SPDT Dry, 2 Amp @ 30VDC (38.1 H x 148.8 W x 38.1 D mm)

Operating Temp: -20° F to 120° F (-29° C to 49° C)

Dimensions: 1.5" H x 6.25" W x 1.5" D

RETROFIT BACK BOX



BB1D

BB1D	Single Gang 2.25" w x 3.75" h x 2.75" D			15.00
------	---	--	--	-------

400 Series EXIT SWITCHES continued

Distributor Discount Code **CK**



430 430N



432KLD

430 SERIES - 1-1/2" MUSHROOM EXIT SWITCH - FOR OPTIONS SEE BELOW						LIST
1.5" Mushroom, Green Button Standard, Dull Stainless Steel Finish, Specify R For Optional Red Button						
1 Gang	Narrow	2 Gang	Contact	Sign		
431CU	431CNU		AA (On/Off) NC SPST	NONE		122.00
431OU	431ONU		AA (On/Off) NO SPST	NONE		122.00
432CU	432CNU		Momentary NC SPST	EXIT		122.00
432OU	432ONU		Momentary NO SPST	EXIT		122.00
432KUR	432KNUR		Latching/ key reset DPST, Red	NONE		239.00
432KLDUR			Lockdown, DPST, Key Reset	LOCKDOWN	UL 294	256.00
432KLDURL2			Lockdown, DPST ,Key Reset, 1 Red and 1 Green LED	LOCKDOWN		291.00
		433U	Momentary with Timer Module 1-60 sec. EXIT 12/24V AC/DC SPDT 2A Contact			228.00
434U	434NU		Momentary DPST	EXIT		150.00
435U	435NU		AA (On/Off) DPST	NONE		150.00

440 SERIES - 2-5/8" MUSHROOM EXIT & PANIC SWITCHES - FOR OPTIONS SEE BELOW



441 - 444 446


440 SERIES - 2-5/8" MUSHROOM EXIT & PANIC SWITCHES - FOR OPTIONS SEE BELOW						LIST
2-5/8" Mushroom, Red Button Standard, Dull Stainless Steel Finish, Specify G For Optional Green Button						
1 Gang	2 Gang		Contact	Sign		
	441U		AA (On/Off) DPST	NONE		211.00
	442U		Momentary DPST	EXIT		211.00
	443U		Momentary with Timer Module 1-60 sec. EXIT 12/24V AC/DC SPDT 2A Contact			305.00
	444U		Momentary 2-DPST	EXIT		234.00
446U			Momentary DPST	EXIT		139.00

OPTIONS AND FINISHES FOR 410,420, 430, AND 440 SERIES

Options for 410, 420, 430, 440 Series						Add to List
L1G	1 Green LED	23.00	LT	Tricolor LED - Red, Green, Amber	34.00	
L1R	1 Red LED	23.00	E	Add Exit sign To AA Function Switch Only	13.00	
L2	1 Red and 1 Green LED	34.00	B	No Exit sign (None) with Momentary Switch	N/C	

Special Finish
 450 / 460 / 470 Special finish is not available
 Designate special finish suffix from below in lieu of U (stainless steel) in part number.

C 605 Bright Brass	D 606 Dull Brass	45.00
P 625 Bright Chrome	H 613 Oil Rubbed Bronze	45.00



463 463N

463 SERIES - VANDAL RESISTANT STAINLESS STEEL EXIT SWITCH						LIST
Capacitive Stainless Steel Button - No moving parts - Integrated Time Delay - Red and Green Status Indicators						
2mm Stainless Steel - Security Screws - Plated Finish Not Available						
1 Gang	Narrow		Contact	Sign		
463U	463NU		Integrated 1-40 Sec Timer 12/24VDC,SPDT 1A Contact	PUSH TO EXIT		145.00



474 474D

474 NO TOUCH SWITCH SERIES - WAVE-TO-OPEN SWITCHES

474 Touchless Switches use Active IR Sensor Technology. A simple wave in front of the 474 Touchless Switch activates the switch to control electric locks/ strikes, magnetic locks, or automatic door operators for entry or egress.

- Adjustable 2"-7" Activation Read Range
- Dual LED, Illuminated Sensor for Status Indication

Output: SPDT 3 Amp Dry Contact
Input: 25mA (standby); 55mA (active) @ 12/24VDC
Faceplate: 20ga Stainless Steel

		Contact	Sign	
474U	1 gang faceplate	SPDT	WAVE TO OPEN	82.00
474DU	2 gang faceplate	SPDT	WAVE TO OPEN	142.00
474MU	1 gang with manual override	SPDT / Override Alt-Action SPDT	EXIT	218.00



474MU

Key & Exit Switches