

# 474U Touchless Series Exit Switch

IR Sensor, 4" read range, Wave to Exit Dual LED, illuminated status indication. Control electric locks/strikes, magnetic locks, or automatic door operators. Entry/exit for sanitary environments including: bathrooms, cleanrooms, hospitals, labs, schools, or offices.



474



474D

## FEATURES

- Uses IR Sensor Technology; Device is Active with the Simple Wave of a Hand
- Designed to Control Electric Locks/Strikes, Magnetic Locks, or Automatic Door Operators
- Ideal for Use in Sanitary Applications Such as Cleanrooms, Bathrooms, Food Processing, Hospitals and Labs
- Sensing Range up to 4"
- Mounted on a Durable Stainless Steel Plate
- Dual LED, Illuminated Sensor, Red/Green Indicates Inactive/Active Status
- Quick Connect Screwless Terminal Block for Easy Installation

## SPECIFICATIONS

<b>Input</b>	25mA (Standby); 70mA (Active) @ 12/24VDC
<b>Output</b>	DPDT 3 Amp Dry Contact Resistive
<b>Activation Time</b>	5 Second or as Long as Sensor is Triggered
<b>LED Color</b>	Standby RED; Active Green
<b>Faceplate</b>	20 Ga Stainless Steel
<b>Range</b>	4"
<b>Weight</b>	3 oz.

## MODELS

- 474U** Sanitary Touchless Exit Switch DPDT, 1 Gang faceplate
- 474DU** Sanitary Touchless Exit Switch DPDT, 2 Gang faceplate



