

### For Handicap Access, Automatic Door Activation & Request-to-Exit Applications

- Door Opener Activation
- Automatic Door Activation
- Access Control Request-to-Exit (RTE)
- Door Sequencer Activation



= can be used with wireless transmitter and receiver

### SPECIFICATIONS

<b>Mounting Plate</b>	Heavy Duty 1/8" (3.2mm) mounting plate
<b>Faceplate</b>	Heavy 18 Gauge (1.02mm), 630/US32D Satin Stainless Steel Standard
<b>Legends</b>	Bold debossing or engraving with black, blue or white infill
<b>Contacts</b>	SPDT or DPDT, 15 Amps @ 125/250VAC; UL 1054, CSA Listed
<b>Depth</b>	[Narrow & (1) Gang] SPDT-7/8" deep, DPDT-1-3/8" deep, [4 1/2", & 6" square/ round] SPDT-3/4" deep, DPDT-1-5/32"



### 1-11/16" Narrow Mullion Push Plate Switch – Recessed, Surface Box or Bollard Mount

SPDT Model	Description	DPDT Model	Description
<b>482O1U</b>	Push to Open, black infill <b>69.00</b>	<b>484O1U</b>	Push to Open, black infill <b>96.00</b>
<b>482A1U</b>	Push to Open, blue infill <b>69.00</b>	<b>484A1U</b>	Push to Open, blue infill <b>96.00</b>
<b>400-1B</b>	Narrow Mullion Surface Box, 1-3/4" x 4-9/16" x 1-3/4" O.D.		<b>30.00</b>



### 2 3/4" x 4 1/2" Single (1) Gang Push Plate Switch

- Pressing any part of the push plate (2 3/4" x 4 1/2") causes switch actuation
- Recessed, Surface Box or Bollard Mount
- Depth: SPDT - 7/8" deep; DPDT - 1 1/2" deep


SPDT Model	Description	DPDT Model	Description
<b>482O2U</b>	Push to Open, black infill <b>83.00</b>	<b>484O2U</b>	Push to Open, black infill <b>110.00</b>
<b>482A2U</b>	Push to Open, blue infill <b>83.00</b>	<b>484A2U</b>	Push to Open, blue infill <b>110.00</b>
<b>480-2SB</b>	Surface mount box, 2 3/4" x 4 1/2" x 1 5/8" O.D.		<b>31.00</b>



### 4 1/2" x 4 1/2" Square Push Plate Switches

- Pressing any part of the push plates 4 1/2" x 4 1/2" active area causes switch actuation
- 1 Gang or 2 gang recessed or Surface Box Mount
- Depth: SPDT 7/8" deep; DPDT 1 1/2" deep

SPDT Model	Description	DPDT Model	Description
<b>482O4U</b>	Push to Open, black infill <b>89.00</b>	<b>484O4U</b>	Push to Open, black infill <b>116.00</b>
<b>482A4U</b>	Push to Open, blue infill <b>89.00</b>	<b>484A4U</b>	Push to Open, blue infill <b>116.00</b>
<b>480-4FB</b>	Square Flush Recessed box, 6 3/4" x 6 3/4" x 2-1/8" O.D.		<b>67.00</b>
<b>480-4SBB</b>	Surface mount box, 4-1/2" x 4-1/2" x 1 3/4" O.D. with Battery compartment for wireless		<b>42.00</b>
<b>480-4SB</b>	Surface mount box, tmper resistant, 5-1/2" x 5-1/2" x 2-1/8" O.D.		<b>67.00</b>
<b>480-4SE</b>	3-sided stainless shroud for exterior applications, 4-11/16" x 4-7/8" x 12"		<b>41.00</b>



### 6" x 6" Square Push Plate Switch

- Pressing any part of the push plates 6" x 6" active area causes switch actuation
- 1 Gang or 2 gang recessed or Surface Box Mount
- Depth: SPDT 7/8" deep; DPDT 1 1/2" deep

SPDT Model	Description	DPDT Model	Description
<b>482O6U</b>	Push to Open, black infill <b>96.00</b>	<b>484O6U</b>	Push to Open, black infill <b>122.00</b>
<b>482A6U</b>	Push to Open, blue infill <b>96.00</b>	<b>484A6U</b>	Push to Open, blue infill <b>122.00</b>
<b>480-6SBB</b>	Surface mount box, 2-gang Battery Compartment, 4 1/2" x 4 1/2" x 1 3/4" O.D.		<b>42.00</b>

## 480 Series Push Plate Switches - Wireless and Hardwired (continued)

Distributor Discount Code **CK LIST**



### 4 1/2" Round Push Plate Switch

- Pressing any part of the push plates 4" 1/2 active area causes switch actuation
- 1 Gang recessed or Surface Box Mount • Depth: SPDT 7/8" deep; DPDT 1 1/2" deep

SPDT Model	Description	DPDT Model	Description
482O4RU	Push to Open, black infill	484O4RU	Push to Open, black infill
482A4RU	♿ Push to Open, blue infill	484A4RU	♿ Push to Open, blue infill
480-4RSB	Surface box, 5" Dia., 2 1/8" O.D.	480-4RFB	Black Flush Escutcheon, 6 3/8" overall diameter with trim ring
480-4RG	4" round gasket for 4RSB or 4RFB box		



### 6" Round Push Plate Switch

- Pressing any part of the push plates 6" active area causes switch actuation
- 1 Gang or 2 gang recessed or Surface Box Mount • Depth: SPDT 7/8" deep; DPDT 1 1/2" deep

SPDT Model	Description	DPDT Model	Description
482O6RU	Push to Open, black infill	484O6RU	Push to Open, black infill
482A6RU	♿ Push to Open, blue infill	484A6RU	♿ Push to Open, blue infill
480-6RSB	Surface box Round, 6 7/16" Dia., 2 1/8" Depth	480-6RFB	Recessed Flush Escutcheon, 7 3/4" overall diameter with trim ring
480-6RG	6" round gasket for 6RSB or 6RFB		

## 480 Series Push Plate Switches - HDPE (High Density Polyethylene)

Distributor Discount Code **CK LIST**



### 4 1/2" x 4 1/2" Square Push Plate Switches

- Pressing any part of the push plates 4" 1/2" x 4" 1/2" active area causes switch actuation
- 1 Gang recessed or Surface Box Mount • Depth: SPDT 3/4" min; DPDT 1-5/32" min

SPDT Model	Description	
482A4SPH	Push to Open, white infill on blue HDPE, SPDT	156.00
484A4SPH	Push to Open, white infill on blue HDPE, DPDT	156.00
480-4FB	Square Flush Recessed box, 1-gang, 6 3/4" x 6 3/4" x 1 7/8" O.D.	67.00
480-4SBB	Surface mount box, 4-1/2" x 4-1/2" x 1 3/4" O.D. with Battery compartment for wireless	35.00
480-4SB	Surface mount box, tamper resistant, 5-1/2" x 5-1/2" x 2-1/8" O.D.	67.00



### 6" Round Push Plate Switch

- Pressing any part of the push plates 6" active area causes switch actuation
- 1 Gang or 2 gang recessed or Surface Box Mount • Depth: SPDT 7/8" deep; DPDT 1-5/32"

SPDT Model	Description	
482A6RPH	Push to Open, white infill on blue HDPE, SPDT	187.00
484A6RPH	Push to Open, white infill on blue HDPE, DPDT	187.00
480-6RSB	Surface box Round, 6 7/16" Dia., 2 1/8" Depth (not shown)	60.00
480-6RFB	Recessed Flush Escutcheon, 7 3/4" overall diameter with trim ring	67.00
480-6RG	6" round gasket for 6RSB or 6RFB	18.00



**482A4VWU**



**482A4VWPU**



**482A4VPU**



**482A4VWPB**



**4 1/2" x 4 1/2" Square Push Plate Switches**

- Pressing any part of the split push plates active area causes switch actuation
- 2 Gang Wall-mount or Surface Box Mount • Depth: 2x SPDT 7/8" deep

**SPDT Model Description**

<b>482A4VWU</b>	♿ Arrow (left/right), blue infill	<b>405.00</b>
<b>482A4VWPU</b>	♿ Arrow (left/right) Push to Open, blue infill	<b>405.00</b>
<b>482A4VPU</b>	Arrow (left/right) Push to Open, black infill	<b>405.00</b>
<b>482A4VWPB</b>	♿ Arrow (left/right) Push to Open, white infill on blue	<b>468.00</b>



<b>480-4SBB</b>	Surface mount box, 4-1/2" x 4-1/2" x 1 3/4" O.D. with Battery compartment for wireless	<b>35.00</b>
-----------------	--	--------------

**Applications**

- Wireless & Hardwire
- ADA Ingress/R.E.X/Egress Door Opener Activation
- Access Control Request-to-Exit (REX)
- Door Opener Activation
- Automatic Door Activation or Lock Release
- Automatic Door & Exit Device Sequencer Activation



= can be used with wireless transmitter and receiver

**Features**

- Surface wall mount or bollard mount
- Sleek Architectural profile
- No square edges to snag, wide sloping sides deflects impact movement naturally to activate column
- Deflects impact from wheeled carts and conveyances
- Impact & Vandal resistant design, inhibits prying, tampering
- Weather Resistant, no gaps for water or ice penetration
- Choice of SPDT or DPDT, 15 Amps @ 125/250VAC



9" X 6" INGRESS-R.E.X TOUCH PANEL COLUMN

List

**Fully Active 22-1/2 Sq. Inch Actuation Area**  
Recommended Centerline mounting height 34" to 48"

**Material:** Sturdy 1/8" extrusion with architectural finish  
**Overall Size:** 9" h x 6" w x 1-1/2" d (229 x 152 x 38mm)  
**Active Area:** 9" h x 2-1/2" w (229 x 63.5mm)

SPDT Model	Description			
482AA9	Push to Open			309.00
SPECIFY FINISH				Add to List
V 628 Aluminum (standard), blue infill	N/C	X 613 Dark Bronze, white infill		26.00



36" X 6" INGRESS-R.E.X TOUCH PANEL COLUMN

List

**Fully Active 90 Sq. Inch Actuation Area**  
Recommended mounting height is 3" from floor

**Material:** Sturdy 1/8" extrusion with architectural finish  
**Overall Size:** 36" h x 6" w x 1-1/2" d (914 x 152 x 38mm)  
**Active Area:** 36" h x 2-1/2" w (914 x 63.5mm)

SPDT Model	Description	DPDT Model	Description	
482AA36	Push to Open	484AA36	Push to Open	433.00 460.00
SPECIFY FINISH				Add to List
V 628 Aluminum (standard), blue infill		X 613 Dark Bronze, white infill		N/C

400 Series Wireless Transmitter and Receiver

For Remote Control Versatility for Touch Panel Column and Push Plate Switches

**433MHz Micro Transmitter**

- Requires a non-metallic surface box or standard bollard cap (non-metallic). Works with 400RC433
- Pre-Wired for quick installation
- Antenna magnifies signal

**Voltage Input:** 9V Battery (included)  
**Trigger Input:** Momentary, N.O.Dry Contact  
**Temperature:** -20F — 100F  
**Dimensions:** 1-9/64" x 15/16" x 7/32" (29 x 49 x 6mm)

Model	Description	
400W1-433	433MHz Micro Transmitter	141.00

**433MHz 1 Channel Nano Receiver**

- Designed to control automatic closing and anti-burglar systems. Works with 400W1-433.

**Carrier Frequency:** 433.92 MHz  
**Relay Numbers:** 1  
**Temperature:** -4F — 158F  
**Power Supply:** 12/24 VAC/DC  
**Contacts:** C-NO  
**Dimensions:** 1-1/4" x 2" x 3/4" Deep (32 x 51 x 19mm)

Model	Description	
400RC433	433MHz 1 Channel Receiver	174.00

