

# 480AA Series

## Push Panels

SDC's push panels combined with SDC's operator, bollards and locking devices allow for complete access and egress solutions for ADA compliant applications. The contoured profile of SDC's Push Panels allows for activation from any approach and height level. Pressing any part of the touch panel columns will activate the device creating seamless operation for users in ADA applications.

Designed specifically for handicap access, automatic door activation and request-to-exit applications. Pressing any part of plate causes switch activation.



### MODELS

**482AA** Push Panel Actuator, SPDT

**484AA** Push Panel Actuator, DPDT



### STANDARD FEATURES

- Entire panel surface activates switch
- Naturally directs movement toward central activation column
- Sleek architectural profile
- No square edges to snag
- Wide sloping sides deflect impact from wheeled carts and conveyances
- Impact and vandal resistant design inhibits prying and tampering
- Wireless or hardwired
- Weather resistant



## APPLICATIONS

- Surface wall or bollard mount
- Access control request-to-exit (REX)
- Automatic door activation



All can be used with wireless transmitter and receiver. See related products.



## SPECIFICATIONS

	482AA9	484AA9	482AA36	484AA36
<b>Panel</b>	1/8" Aluminum	1/8" Aluminum	1/8" Aluminum	1/8" Aluminum
<b>Dimensions</b>	9" x 6"	9" x 6"	36" x 6"	36" x 6"
<b>Sign</b>	♿ PUSH TO OPEN	♿ PUSH TO OPEN	♿ PUSH TO OPEN	♿ PUSH TO OPEN
<b>Sign Infill</b>	Blue	Blue	Blue	Blue
<b>Weight</b>	4 lbs	4 lbs	7 lbs	7 lbs
<b>Contact</b>	SPDT	DPDT	SPDT	DPDT
<b>Rating</b>	15 Amp @ 125/250 VAC Resistive	15 Amp @ 125/250 VAC Resistive	15 Amp @ 125/250 VAC Resistive	15 Amp @ 125/250 VAC Resistive
<b>Type</b>	Momentary (MO)	Momentary (MO)	Momentary (MO)	Momentary (MO)
<b>Depth</b>	1 1/2"	1 1/2"	1 1/2"	1 1/2"
<b>Operating Environment</b>	-40°F to +221°F	-40°F to +221°F	-40°F to +221°F	-40°F to +221°F

## CERTIFICATIONS

UL1054  
CSA Listed

## HOW TO ORDER

### FOLLOW STEPS FOR ORDERING

   Designates optional step

#### 1| SPECIFY MODEL

- 482** Push Actuator, SPDT
- 484** Push Actuator, DPDT

#### 3| SPECIFY SIZE

- A9** Panel, 9" x 6"
- A36** Panel, 36" x 6"

#### 2| SPECIFY SIGN

- A** ♿ PUSH TO OPEN

#### 4| SPECIFY FINISH

- V** 628 Dull Aluminum Standard
- X** 710 Dark Bronze

STEP NUMBER:	1	2	3	4
ORDERING EXAMPLE:	<b>482</b>	<b>A</b>	<b>A36</b>	<b>V</b>

## RELATED PRODUCTS

### WIRELESS TRANSMITTERS & RECEIVERS

- 400RC433** 433MHz One Channel Receiver
- 400W1-433** 433MHz Micro Transmitter

