

480PH Series

HDPE Push Plates



SDC's HDPE push plate actuators combined with SDC's operator, bollards and locking devices allow for complete access and egress solutions for ADA compliant applications. Included are round and square options. High Density Polythethylene (HDPE) push plates are recyclable, non-polluting, have outstanding longevity and are made from environmentally sound polymers. HDPE push plates are antimicrobial and contain no known harmful substances, including carcinogens or toxins. Also, HDPE push plates are extremely durable which maximizes product lifecycles and reduces overall impact on the environment.

Designed specifically for handicap access, automatic door activation and request-to-exit applications. Pressing any part of plate causes switch activation.

MODELS

482 Push Plate Actuator, SPDT

STANDARD FEATURES

- Entire plate surface activates switch
- SPDT contact
- Round or square
- Bold debossed sign legends
- White infill
- Wireless or hardwired
- HDPE - high density polyethylene
- Weather resistant
- Anti-microbial & scratch resistant



APPLICATIONS

- Recessed, surface box or bollard mount



All can be used with wireless transmitter and receiver. See related products.



482A4SPH



482A6RPH

SPECIFICATIONS

	482A4SPH	482A6RPH
Plate Size	Double Gang, Square	Triple Gang, Round
Faceplate	HDPE, Blue	HDPE, Blue
Dimensions	4½" x 4½"	6"
Mounting	Single gang recessed or surface box	Single or double gang recessed or surface box
Contact	SPDT	SPDT
Rating	1 Amp @ 28 VDC Resistive	1 Amp @ 28 VDC Resistive
Type	Momentary (MO)	Momentary (MO)
Depth	¾"	⅞"

CERTIFICATIONS

UL1054

CSA Listed

HOW TO ORDER

FOLLOW STEPS FOR ORDERING

Designates optional step

1| SPECIFY MODEL

482 Push Actuator, SPDT

2| SPECIFY SIGN

A & PUSH TO OPEN

3 | SPECIFY FACEPLATE

4SPH Square, 4½" x 4"½"

6RPH Round, 6" Diameter

STEP NUMBER:	1	2	3
ORDERING EXAMPLE:	482	A	4SPH

RELATED PRODUCTS

WIRELESS TRANSMITTERS & RECEIVERS

400RC433 433MHz One Channel Receiver

400W1-433 433MHz Micro Transmitter



4½" SQUARE MOUNTING

480-4FB Flush Recessed Box, 6¾" x 6¾" x 2⅛"

480-4SBB Surface Box with Battery Compartment, 4½" x 4½" x 1¾"

480-4SB Surface Box, 5½" x 5½" x 2⅛"

480-4SE Three Sided Shroud, 4⅞" x 4⅞" x ½"



6" ROUND MOUNTING

480-6RSB Surface Box, 6⅞" x 2⅛"

480-6RG Gasket for 480-6RSB or 480-6RFB, 6"

480-6RFB Flush Recessed Escutcheon, 7¾"

