

480V Series

Vestibule Push Plates

SDC's vestibule push plate actuators combined with SDC's operator, bollards and locking devices allow for complete access and egress solutions for ADA compliant applications. Vestibule push plates feature two separate face plate switches that will allow for independent activation of two automatic doors. Available in various display verbiage, logo and markings. All vestibule push plates can be wireless or hardwired, bollard or wall mounted.

Designed specifically for handicap access, automatic door activation and request-to-exit applications. Pressing any part of plate causes switch activation.



MODELS

482A4VWPU ♿ ↔ PUSH TO OPEN

482A4VPU ↔ PUSH TO OPEN

482A4VWPB ♿ ↔ PUSH TO OPEN, Blue

STANDARD FEATURES

- Entire plate surface activates switch
- SPDT contacts
- Split plates for vestibule applications
- Bold debossed sign legends
- Blue, black and white infills
- Wireless or hardwired
- Weather resistant



APPLICATIONS

- Recessed, surface box or bollard mount



All can be used with wireless transmitter and receiver. See related products.



482A4VWPU



482A4VPU



482A4VWPB

SPECIFICATIONS

	482A4VWPU	482A4VPU	482A4VWPB
Plate Size	Double Gang, Square	Double Gang, Square	Double Gang, Square
Faceplate	18 Guage Stainless Steel	18 Guage Stainless Steel	18 Guage Stainless Steel (Blue Powder Coat)
Dimensions	4 1/2" x 4 1/2"	4 1/2" x 4 1/2"	4 1/2" x 4 1/2"
Mounting	Double gang recessed or surface box	Double gang recessed or surface box	Double gang recessed or surface box
Contact	SPDT (2)	SPDT (2)	SPDT (2)
Rating	2 Amp @ 48 VDC Resistive	2 Amp @ 48 VDC Resistive	2 Amp @ 48 VDC Resistive
Type	Momentary (MO)	Momentary (MO)	Momentary (MO)
Depth	7/8"	7/8"	7/8"

CERTIFICATIONS

UL1054
CSA Listed

HOW TO ORDER

FOLLOW STEPS FOR ORDERING

 Designates optional step

1| SPECIFY MODEL

482A4VWPU PUSH TO OPEN

482A4VPU PUSH TO OPEN

482A4VWPB PUSH TO OPEN, Blue

STEP NUMBER: 1

ORDERING EXAMPLE: **482A4VWPU**

RELATED PRODUCTS

WIRELESS TRANSMITTERS & RECEIVERS

400RC433 433MHz One Channel Receiver

400W1-433 433MHz Micro Transmitter



MOUNTING

480-4SBB Surface Box with Battery Compartment,
4 1/2" x 4 1/2" x 1 3/4"

