


### LOW-ENERGY, HANDS-FREE CONVENIENCE & ADA COMPLIANCE



Besides having the best warranty and lowest price of any competitive low-energy door operator in the industry, the AutoEntryControl™ Swinging Door Operator has all the features you'd expect from full power systems without the installation headaches and maintenance commitments.

- Extremely Quiet Operation
- Night mode control option
- Single-person, low-cost install
- No maintenance contract required
- One-button, hassle-free setup
- Three Year Warranty

Low-Power Door Operator COMPARISON	LCN	HAGER	DESK	LCN	LCN	Norton ASSA ABLOY	Norton ASSA ABLOY	DORMA	SDC
	Sr. Swing 9500	8400	AO-19	Benchmark 9100	AE	5900	6000	ED900	Auto 1/2
One-button Setup		✓							✓
Non-handed				✓	✓	✓	✓	✓	✓
Push or Pull Same Unit			✓	✓	✓	✓	✓	✓	✓
Momentary Closing Force Prior to Unlocking								✓	✓
Built in Delay to Retract Strike or Mag Lock	✓	✓	✓	✓	✓	✓	✓	✓	✓
Three Year Warranty			✓ <small>*Mechanical Only</small>						✓
List Price	\$4,322	\$4,226	\$3,400	\$3,308	\$5,179	\$3,646	\$5,112	\$5,089	<b>\$2,339</b>



# SDC AUTO EntryControl™

Security Door Controls

The state-of-the-art microprocessor-based unit is self-tuning and self-learning while offering non-handed operation, full mechanical stops and a variety of interface options for sensors, push-plates, fire alarms and electrified locks.

**Perfect for healthcare facilities, retail storefronts, office buildings, & campuses.**

Low-Power Door Operator COMPARISON	LCN. Sr. Swing 9500	HAGER 8400	DELEX AO-19	LCN. Benchmark 9100	LCN. AE	Norton ASSA ABLOY 5900	Norton ASSA ABLOY 6000	DORMA ED900	SDC Auto 1, 2
Three Year Warranty	2 yr	2 yr	mechanical only	2 yr	2 yr	2 yr	2 yr	1 yr	✓
Non-handed				✓	✓	✓	✓	✓	✓
Push or Pull Same Unit			✓		✓	✓	✓	✓	✓
High Traffic Use	✓	✓	✓	✓	✓	✓	✓	✓	✓
One-button Setup		✓							✓
Momentary Closing Force Prior to Unlocking		✓						✓	✓
Built in Delay to Retract Strike or Mag Lock	✓	✓	✓	✓	✓	✓	✓	✓	✓
Max. Door Weight (lbs.) (36" opening)	200	350	200	200	200	200	250	220	342
Electric Lock Power	✓	✓	✓	✓	✓	✓	✓	✓	✓
Total Power Required @ 115vac (Watts)	300	300	300	120	120	75	108	120	100
Manual Opening Force < 15 pounds	✓	✓	✓	✓	✓	✓	✓	✓	✓
Adjustable Opening Speeds	✓	✓	✓	✓	✓	✓	✓	✓	✓
Up to 48" Single Door Openings	✓	✓	✓	✓	✓	✓	✓	✓	✓
Complies w/ ANSI 156.19	✓	✓	✓	✓	✓	✓	✓	✓	✓
ADA Compliant	✓	✓	✓	✓	✓	✓	✓	✓	✓
UL Fire Rated for 3 hr doors	✓	✓	✓	✓	✓	✓	✓	✓	✓
Electro-Mechanical	✓	✓	✓	✓		✓		✓	✓
Surface Applied	✓	✓	✓	✓	✓	✓	✓	✓	✓
Full Length Header	✓	✓	✓	✓		✓	✓	✓	✓
Activation: Knowing Act	✓	✓	✓	✓		✓	✓	✓	✓
Push n Go Operation	✓	✓	✓	✓	✓	✓	✓	✓	✓
Auto-Reverse	✓	✓	✓	✓		✓	✓	✓	✓
Obstruction Stop	✓	✓	✓	✓	✓	✓	✓	✓	✓
Microprocessor Control	✓	✓	✓	✓	✓	✓	✓	✓	✓
Programmable Controls	✓	✓	✓	✓	✓	✓	✓	✓	✓
Built in Interface for Header Mounted Presence Sensor		✓	✓			✓	✓	✓	✓
Diagnostic evaluation		✓	✓	✓	✓	✓	✓	✓	✓
Electro-Hydraulic	✓				✓		✓		

