

# 30 Series

## 3/4" Pullman Latchbolt Electric Strikes



SDC's 30 series 3/4" pullman latchbolt electric strikes are designed for use with rim mount exit devices having pullman type latchbolts. 30 series strikes accept 3/4" throw pullman style latchbolts.

Built with all stainless steel parts and stainless steel housing for maximum lifespan, corrosion and tamper resistance, the heavy duty construction makes 30 series strikes ideal for high traffic applications. Additionally, 30 series strikes feature in-frame horizontal adjustability, set screws to allow for adjustment lockdown, milled ramps to better accommodate deadlatches, and an integrated space plate shim for quick customization of faceplate thickness,

**30 series strikes come standard in failsecure operation and are fire-rated.** Failsecure operation unlocks the keeper when energized and locks the keeper when de-energized or during power failure.

Failsafe operation is optional but is not permitted with UL fire door accessory label. Failsafe operation locks the keeper when energized and unlocks when de-energized or during a power failure.

**30 series strikes are not compatible with SDC's S6000 exit devices.** Utilize 30 series template to confirm exit device compatibility before ordering.



### MODELS

**30-4** 3/4" Pullman Latchbolt Strike



### STANDARD FEATURES

- Pullman keeper
- Stainless steel components
- Stainless steel housing and faceplate
- Corrosion and tamper resistant
- Horizontal alignment adjustment
- Integrated spacer plate shim
- Non-handed
- Internally mounted solenoid
- Failsecure operation
- Voltage and current spike protection
- Pigtail connectors



### OPTIONAL FEATURES

- Failsafe operation
- Latch and keeper deadlocked status



## SPECIFICATIONS


	<b>30-4</b>
<b>Latchbolt</b>	¾" Throw, Pullman Style
<b>Static Strength</b>	1,500 lbs
<b>Dynamic Strength</b>	70 lbs
<b>Endurance Cycles</b>	500,000
<b>Keeper Depth</b>	¾"
<b>Dimensions</b>	9" x 1¾" x 2½"
<b>Weight</b>	4 lbs
<b>Input</b>	12/24 VDC ± 10%
<b>Current Draw</b>	510 mA @ 12 VDC 250 mA @ 24 VDC
<b>Monitoring Contacts</b>	SPDT 3 Amps @ 30 VDC Resistive

## CERTIFICATIONS

UL 294 Access Control System Units  
 UL 1034 Burglary-Resistant Electric Locking Mechanisms  
 UL 10B Fire Tests of Door Assemblies  
 UL 10C Positive Pressure Fire Tests of Door Assemblies  
 ANSI/BHMA A156.31 Grade 1


## HOW TO ORDER

### FOLLOW STEPS FOR ORDERING

 Designates optional step

**1| SPECIFY MODEL**  
**30-4** ¾" Pullman Latchbolt Strike

**2| SPECIFY VOLTAGE**  
**-12** 12 VDC  
**-24** 24 VDC

**3| SPECIFY FINISH**  
**U** 630 Dull Stainless 

**4| SPECIFY OPTIONS**  
**FS** Failsafe Operation  
**LCBMA** Latch & Keeper Deadlocked Status

STEP NUMBER:	1	2	3	4
ORDERING EXAMPLE:	<b>30-4</b>	<b>-24</b>	<b>U</b>	<b>LCBMA</b>

## RELATED PRODUCTS

BRIDGE RECTIFIERS  
**BR64XL** AC to DC Bridge Rectifier

