



# COMPETITIVE COMPARISON

## 1511S Series Integrated Delayed Egress Locks



	CX-DE1200	1200DE	1511S
Years in the Market	< 1	<1	20+
Digital Countdown Display	No	✓	✓
Holding Force (lbs)	1200	1200	1650
Max Current Draw (@12/24VDC, 1200lb)	600mA / 330mA	825mA / 490mA	400mA / 275mA
Trigger Sensor	Hall Effect Proximity, Adjustable	Mechanical Plunger Switch	Hall Effect Proximity, Adjustable
Reset & REX with Single Input	No	✓	✓
UL listed	UL294	UL294, UL10C	UL294, UL10C
Warranty	3 yrs	Limited Lifetime	5 yrs
Auto-Relock	✓	✓	✓
Remote Reset	✓	✓	✓
Remote Trigger	✓	✓	✓
External Speaker Output	✓	No	✓
Alarm Output	✓	✓	✓
Lock Secure Output	✓	✓	✓
FACP Input	✓	✓	✓
Interlocking Mounting Plate	✓	✓	✓
Tandem Available	✓	No	✓ 1511T
Field Interchangeable Applications	No	No	✓
Multiple Finishes Available	No	No	✓
Patient/Infant Protection Compatible	No	✓	✓





# COMPETITIVE COMPARISON

	CX-DE1200	1200DE	1511S
Housing Material	Aluminum	Aluminum	Aluminum
Dimensions	11" x 3" x 3"	10 1/2" x 2 7/8" x 2 3/4"	11" x 2 3/4" x 2 5/8"
Weight (lbs)	15	15	14
Operating Voltage	12/24 VDC, Auto-Sensing	12/24 VDC, Auto-Sensing	12/24 VDC, Auto-Sensing
Delay Time	Adjustable, 15 or 30 Seconds	Adjustable, 15 or 30 Seconds	Adjustable, 15 or 30 Seconds
Nuisance Delay	Adjustable or Fixed	Adjustable or Fixed	Adjustable or Fixed
Audible Instructions	Male or Female Voice; or Tone Only	Voice or Tone Only	Male or Female Voice; or Tone Only
DPS Output	Standard	Standard	Optional
BAS Output	Standard	No	Optional
Anti-Tamper	Standard	Standard	Optional
Alternative Languages	Standard	Standard	Optional
Power-Up Mode	Locked or Bypassed	Locked or Bypassed	Locked or Bypassed
Code Compliance	NFPA, UBC, IBC, CBC, BOCA, Chicago	NFPA, UBC, IBC, CBC, BOCA, Chicago, CSFM	NFPA, UBC, IBC, CBC, BOCA, Chicago, CSFM

Specifications are subject to change without notice.

