



PUBLIC VENUES MARKET APPLICATIONS

Outdoor Gate Control









The use of a hydraulic gate closer is highly recommended for swinging gate applications.

1 1575 / 1576 Series

Electromagnetic Gate Locks

1575U Single Gate Lock1576U Single Gate Lock, Face-Drilled



- · 1,200lb holding force
- Weatherized
- Monitoring standard

2 926 Series

Outdoor Digital Keypads

926 Standalone, Self-Contained



- Surface wall or post mount
- Weather and vandal resistant
- 500 users

3 MSB550 Series

Mechanical Switch Bars

MSB550-2WV42 Weatherized, 42"

MSB550-2WV48 Weatherized, 48"



- 1/8" total bar movement
- Heavy duty aluminum extrusion
- Metal end caps

4 602 Series

1 Amp Power Controllers

602RF	Controller with Cabinet
RB12V4	12V/5Ah Battery
RB12V4-2	12V/5Ah Battery, Qty 2



- Regulated and filtered linear DC power
- Field selectable dual voltage (12/24 VDC)
- Fire/emergency release input

SELECT ONE

5 480 Series

Push Plate Actuators

48201U	Narrow, PUSH TO OPEN
48202U	Single Gang, PUSH TO OPEN
48204U	41/2" Square, PUSH TO OPEN



- PUSH-TO-OPEN
- Recessed, surface and bollard mounting

5 460 Series

Capacitive Touch Sensors

463NU	Narrow
463U	Single Gang



- Integrated adjustable timer
- Selectable bicolor illumination status
- Adjustable timer or alternate action