



## MITIGATE LIABILITY, ENSURE FUNCTIONALITY

Door-Mounted  
Presence Sensors  
for Door Operators

**AUTO-IR36Y**  
Presence Sensor, 36"

**AUTO-IR48Y**  
Presence Sensor, 48"

### WHAT YOU NEED TO KNOW:

**Every low energy door operator should be ordered with an AUTO-IR presence sensor to mitigate liability.**

The AUTO-IR accessory mitigates liability through re-activation of door before contact is made during the closing cycle, protecting slow-moving people as well as people trailing behind. It reliably detects stationary as well as moving objects in the swing path of an automatic door. When using the AUTO-IR mounted on the application side of the door, the need for an extended hold open time is eliminated, allowing the door to begin the close cycle after the minimum 5 second hold open time has elapsed.

Using the AUTO-IR presence sensor exceeds ANSI 156.19 standards by offering a contactless experience, further mitigating liability.

### HOW YOUR CUSTOMER BENEFITS:

- Simple, one-button calibration setup
- Dual sensors to ensure presence activation\*
- Smooth and safe operation of door
- Exceeds ANSI 156.19 standards
- Proven active IR technology for distance measurement through triangulation
- Optional programming to customize settings

\* AUTO-IR48 models only.

[sdcsec.com/AUTO-IR](https://sdcsec.com/AUTO-IR)



# Need Help Building Your Solution?

Use **DoorSnap™** in the free **SDC App** for your door retrofit projects



SDC Solution Experts Will Craft Personalized Solutions For You!

- 1 Open the SDC App and select DoorSnap™
- 2 Take a photos of your door opening
- 3 Submit photos of your door opening
- 4 Receive a complete access and egress electrified solution

Download the FREE SDCSecurity App now!

Our award-winning app includes labor-saving DoorSnap™ functionality. SDC will recommend a cost effective solution with product information links to retrofit the opening for access & egress control locking hardware.

