



SDC's HiShear[®] electromagnetic shear locks are designed, engineered

1562SC Series

Semi-Concealed Electromagnetic Shear Locks

ORDERING GUIDE

and built in America for openings that
require an architecturally superior
appearance. Long recognized as a cut
above alternatives on the market, SDC
shear locks provide high security with
a failsafe locking mechanism to meet a
variety of door opening applications.
SDC's 1562SC series semi-concealed
configuration incorporates the
innovative HiShear [®] concealed

configuration incorporates the innovative HiShear® concealed electromagnetic lock with a surface mounted armature assembly. The semi-concealed design also provides the advantage of mounting the HiShear® on the secure side of the door opening, eliminating potential for tampering.

- Concealed mortise lock and surface mount armature design
- Floating armature assembly
- Special alloy steel shear tabs
- · Auto-sensing dual voltage
- Door alignment relock sensor
- Adjustable lateral and vertical alignment
- Noise dampeners

	FINISH	
	V	
	Y	
	С	
	X	
	Q	
	Р	
1562SCHDB	V	DL
1562SC		D
1562SCHDB		L
1562SCHDB3/4		OPTIONS
MODEL		

MODEL

NOT REQUIRED

1562SCV	Semi-Concealed Shear, External Electronics, 2000lbs, 628	1,070.00
1562SCVD	Semi-Concealed Shear, External Electronics, 2000lbs, 628, DPS	1,132.00
1562SCVDL	Semi-Concealed Shear, External Electronics, 2000lbs, 628, DPS, BAS	1,153.00
1562SCHDBV	Semi-Concealed 1/2" Glass Door Shear, External Electronics, 2000lbs, 628	1,326.00
1562SCHDB3/4V	Semi-Concealed ¾" Glass Door Shear, External Electronics, 2000lbs, 628	1,326.00

EXAMPLES

COMPONENT CONSIDERATIONS

With a robust toolbox of over 35,000 SDC access & control components at your fingertips, you can add additional components to complement the products you're ordering and assemble a turnkey solution for almost any controlled door opening system imagined.



Keypads & Readers Page 101-105



Egress Devices Pages 118-122



Exit Switches & Sensors Pages 123-134



Emergency Door Releases Page 135



Power Controllers Pages 142-153



Door Controllers Page 154



Remote Control Consoles Pages 155-156



Door Prop Alarms & Annunciators Page 157-158

1562SC CONFIGURATION 1 of 1

MODEL	MODEL	
1562SC Semi-Concealed Shear Lock, External Electronics, 2000lbs 1,070		1,070.00
1562SCHDB	1562SCHDB Semi-Concealed ½" Glass Door Shear Lock, External Electronics, 2000lbs	
1562SCHDB3/4	Semi-Concealed ³ /4" Glass Door Shear Lock, External Electronics, 2000lbs	1,326.00

FINISH	$\bigcirc \bullet \bigcirc$	ADD TO LIST
۷	628 Dull Aluminum & Standard	N/C
Y	335 Dull Black	99.00
C	605 Bright Brass	126.00
Х	710 Dark Bronze	99.00
Q	626 Dull Chrome	234.00
Ρ	625 Bright Chrome	234.00

OPTIONS	000	ADD TO LIST
D	Door Position Status (DPS)	62.00
L*	Visual Status Indicator (LED)	21.00

* Mounts separately through the frame and may be used to indicate lock is enegized or wired to monitoring contacts.