



S6300 Series

Electrified Architectural Mortise Exit Devices

SDC's Spectra™ S6300 series electrified architectural mortise exit devices offer several electrified options to complement your access control system and meet virtually any application. UL listed and ANSI/BHMA A156.3 Grade 1 compliant, S6300 series devices comply with all national and state building and fire life safety codes.

Designed for a modern look and quiet push pad operation, S6300 series devices are panic or fire rated exit devices in mortise configurations.

- Electrified architectural design
- Panic and fire rated devices
- Durable stainless steel construction
- Corrosion resistant
- High traffic use

ORDERING GUIDE

MODEL		RATING		FINISH		LENGTH		ELECTRIFICATION		TRIM OPTIONS	
S63	03	P	RR	U	36	R	E	EE	MS		
	08	F	RR	U	42	R	EM	EE	MF		
	14		LR	U	48	L	A	EE			
				LR	U			B	GE		
			HANDING			OPTIONS		TRIM			

NOT REQUIRED

EXAMPLES

S6303PRRU36EEE	Mortise, Nightlatch, Panic, RHRB, 630, 36", Motorized ELR & Dogging	2,196.00
S6303PRRU42EEE	Mortise, Nightlatch, Panic, RHRB, 630, 42", Motorized ELR & Dogging	2,248.00
S6303PRRU48EEE	Mortise, Exit Only, Panic, RHRB, 630, 48", Motorized ELR & Dogging	2,300.00
S6303PRRU36EEMS	Mortise, Nightlatch, Panic, RHRB, 630, 36", Electrified Case, Failsecure	1,624.00
S6303FRRU36EEMF	Mortise, Nightlatch, Fire, RHRB, 630, 36", Electrified Case, Failsafe	1,759.00

S6300 CONFIGURATION 1 of 2



S63



Eclipse Trim



Galaxy Trim



Mortise Key Cylinder

MODEL	● ○ ○ ○ ○ ○ ○ ○ ○ ○ ○ ○	LIST \$
S63	Mortise	1,096.00

FUNCTION	○ ● ○ ○ ○ ○ ○ ○ ○ ○ ○ ○ ○	ADD TO LIST
03	Key Retracts Latchbolt (Nightlatch)	N/C
08*	Key Locks/Unlocks Lever (Classroom)	N/C
14*	Lever Always Active (Passage)	N/C

** Not applicable for use with S6300A or S6300B alarmed exit models.*

RATING	○ ○ ● ○ ○ ○ ○ ○ ○ ○ ○ ○ ○	ADD TO LIST
P	Panic Device <small>☑ Standard</small>	N/C
F	Fire-Rated Device	135.00

HANDING	○ ○ ○ ● ○ ○ ○ ○ ○ ○ ○ ○ ○ ○	ADD TO LIST
RR	Right Hand Reverse Bevel (RHRB)	N/C
LR	Left Hand Reverse Bevel (LHRB)	N/C

FINISH	○ ○ ○ ○ ● ○ ○ ○ ○ ○ ○ ○ ○ ○ ○	ADD TO LIST
U	630 Dull Stainless <small>☑ Standard</small>	N/C

LENGTH	○ ○ ○ ○ ○ ● ○ ○ ○ ○ ○ ○ ○ ○ ○ ○	ADD TO LIST
36	36" Door Opening <small>☑ Standard</small>	N/C
42	42" Door Opening	52.00
48	48" Door Opening	104.00

OPTIONS	○ ○ ○ ○ ○ ○ ● ○ ○ ○ ○ ○ ○ ○ ○ ○ ○	ADD TO LIST
R	Request-To-Exit (REX)	98.00
L	Latch Status (LS)	98.00

ELECTRIFICATION*	○ ○ ○ ○ ○ ○ ○ ● ○ ○ ○ ○ ○ ○ ○ ○ ○ ○	ADD TO LIST
E	Motorized Electric Latch Retraction & Dogging	816.00
EM	Motorized Electric Latch Retraction & Dogging, External Module	876.00
G	Electric Dogging	524.00
A	Alarmed Exit, Battery Powered	477.00
B	Alarmed Exit, Hardwired	524.00

** Specify one electrification option only.*

Continued on next page.

COMPONENT CONSIDERATIONS

With a robust toolbox of over 35,000 SDC access & control components at your fingertips, you can add additional components to complement the products you're ordering and assemble a turnkey solution for almost any controlled door opening system imagined.



Keypads & Readers
Page 101-105



Power Transfer Devices
Page 141



Power Controllers
Pages 142-153



Door Controllers
Page 154



Door Prop Alarms & Annunciators
Page 157-158

S6300 CONFIGURATION 2 of 2

TRIM*	○○○○○○○○●○	ADD TO LIST
EE	Eclipse Escutcheon	284.00
GE	Galaxy Escutcheon	284.00

*Key cylinder not included, order separately.

TRIM OPTIONS*	○○○○○○○○●○	ADD TO LIST
MS	Electrified Case, Failsecure Outside Lever	244.00
MF	Electrified Case, Failsafe Outside Lever	244.00

RELATED PRODUCTS

When you order any SDC products in this section, there are a number of related or complementary products that have proven to work well with your selection.

CYL-6KDQ	Mortise Cylinder, 6-Pin, 1 1/8" Length, Keyed Different	55.00
CYL-6KAQ	Mortise Cylinder 6-Pin, 1 1/8" Length, Keyed Alike	55.00