Restaurant Delivery Doors

- Customer and Employee Safety
- Emergency Unlock and Alarm Annuciator

Employee Backdoor Security Solution



LOCKING & ACCESS CONTROL SOLUTIONS OPTIONS

1 350 Narrow Line EMLock® Single Narrow Line Magnetic Lock • Holding Force- 1200 lbs UL Listed, 12/24 VDC Clear Anodized Aluminum Architecturally Superior Appearance 1 1511 Single EMLock® Single Surface Mounted Magnetic Lock • Holding Force- 1650 lbs 920P EntryCheck™ Keypad & Prox Reader • 500 Users, Keypad Programmable • 12/24 VAC/DC • Heavy Cast Vandal Resistant Housing • Metal Blue Backlit Keys Keypad Tamper Lockout HID Compaticle Proximity Reader **Optional Privacy Shroud** 423MU Request-to-Exit Device C • Single Gang "Request-To-Exit" Switch • 2" square button, wall mount

- Fixed 30 second relock delay & Retriggerable
- 12/24VDC, DPDT, 5A

MD-31D PIR Request-to-Exit Sensor

- 1-60 second relock delay
- · Frame, wall or ceiling mounted
- 12/24V AC/DC, 1A 2 SPDT Dry



The lock behind your system

White or

Black Finish

492 Exit Emergency Pull Station with Siren

- Immediate Unlocking of Perimeter Doors
- Audible Siren
- 10 Amp, 12/24V AC/DC, DPDT
- 2 Replacement Rods Indcluded

602RF 1 Amp Power Supply

- 12/24 VDC, 1 Amp
- Regulated and Filtered
- Emergency Release Input
- UL Listed
- Batteries Optional

RB12V4-2 Backup Batteries

- Two 12V/5Ah Bateries
- Continuous Operation **During Power Failure**
- 40 Hours @ .25 Amp





EA100 Multi-Mode Exit Annunciator

- Visual Multicolor Signal
- Wall, Ceiling, Frame Mount
- 12/24 VDC, Voltage



