



# S4000E Series

Electrified Commercial Exit Device

**PRE-INSTALLED  
POWER & PROFITS  
STANDARD\***



	<b>SARGENT</b> ASSA ABLOY	<b>DETEX</b>	<b>SDC</b> Security Door Controls
	80 Series	V40/V50/V51	S4000E
<b>Pre-Installed Electric Latch Retraction</b>			✓
<b>Electric Latch Retraction</b>	Option	Option	✓ Standard
<b>Electric Dogging</b>	Option	Option	✓ Standard
<b>Request-to-Exit</b>	Option	Option	✓ Standard
<b>List Price (RIM W/ELR &amp; REX)</b>	\$2,836	\$1,467	\$1,339

Specifications			
Door Stile	Wide	Wide (4" Min.)	Wide (4" Min.)
Door Standard Height	7"	7"	7"
Door Standard Width	32", 36", 42", 48"	36", 48"	36"
Door Thickness	1-3/4" to 2-1/4"	1-3/8" to 2-1/4"	1-3/4"
Door Types	HM or Wood	HM, Wood, Fiberglass or AL	HM, Wood or Mineral Core
Device Types	RIM, Mortise, SVR, CVR, Narrow	RIM, SVR	RIM, SVR
Headcover	Stainless Steel	Aluminum	Stainless Steel
Rail	Stainless Steel	Aluminum	Stainless Steel
Pushpad	Stainless Steel	Aluminum	Stainless Steel
Pushpad Protective Guard	Lexan	ABS	Nylon 6/6 (30% Glass Fill)
End Caps	Stainless Steel	Aluminum	Stainless Steel
Projection	Neutral: 3" Depressed: 2-1/8"	Neutral: 3-1/4" Depressed: 2-1/2"	Neutral: 2-7/16" Depressed: 1-11/16"
Warranty	5yr Mechanical & ELR	10yr Mechanical, 3yr Electrical	5 yr

\*The SDC S4000E comes with pre-installed Motorized Latch Retraction and Request-To-Exit standard - making it more cost-effective than competitive exit devices requiring add-on options.

Electrical Specifications			
ELR Input	600mA Inrush, 250mA Continuous @24VDC	2Amp Inrush, 200mA Continuous @24VDC	700mA Inrush, 200mA Continuous @24VDC
REX Output			10Amp @250VAC Resistive

Features			
Trim Options	Lever or Pull	Lever or Pull	Lever
Pre-Installed Electric Latch Retraction			✓
Electric Latch Retraction	Option	Option	✓ Standard
Electric Dogging	Option	Option	✓ Standard
Request-to-Exit	Option	Option	✓ Standard

Regulatory			
UL 305 Listed (Panic)	✓	✓	✓
UL 10C Listed (Fire)	✓	✓	✓
ANSI/BHMA A156.3	Grade 1	Grade 1	Grade 1

