



SDC's WRC Series 2-Channel wireless transmitter/receiver solution is specifically designed to be used as a receptionist button or remote release for single or dual door access control applications.



**433MHZ 2-BUTTON PENDANT TRANSMITTER** LIST

- **Operates with 400WRC-R2**
- **Frequency:** 433.92MHz
- **Housing:** Keychain type
- **Voltage:** 6VDC
- **Battery Replacement:** – CR2016 Button Cell 3V Lithium battery (x 2)
- **Transmitting distance:** 160 feet (no obstructions)
- **Activation:** Hold "A" or "B" button for 1 sec.

Model	Description	
WRC-2B	433MHz 2-Button Pendant Wireless Transmitter	<b>54.00</b>



**433MHZ 2-CHANNEL RECEIVER** LIST

- **Size with housing (approx.):** 2.5" H x 1.75" W x 1.2" D
- **Frequency:** 433.92MHz
- **Environmental:** Indoor
- **Operating Temperature:** -22°F – 140°F
- **Input Voltage:** 24VDC
- **Current consumption:** 9mA @24VDC (standby); 46mA (max)
- **Relay Outputs:** Two (2) Dry, Form C (SPDT)
- **Contact rating:** 10A@30VDC (resistive)
- **Wiring connections:** 12", 8-wire pigtail
- **Transmitter coding capacity:** 30 (fixed code)
- **Transmitter programming using onboard learning button and status LED**

Model	Description	
WRC-R2	433MHz 2-Channel Wireless Receiver	<b>87.00</b>

**Communicating Bathroom Controls**



CB401-A  
CB402-A



CB401-B  
CB402-B

**EmLock®**

<b>CB401-AU</b>	Communicating bath switch, 630 Stainless Steel finish.	<b>128.00</b>
<b>CB401-B</b>	Emergency access switch, red. 2 Required	<b>134.00</b>
<b>CB701</b>	Emergency key switch, red	<b>167.00</b>

**Electrified Lockset, HiTower® , or Strike Application**

<b>CB402-A</b>	Communicating bath switch, U 630 Stainless Steel finish.	<b>128.00</b>
<b>CB402-B</b>	Emergency access switch, red. 2 Required	<b>134.00</b>
<b>CB702</b>	Emergency key switch, red	<b>167.00</b>